DT 4 4 4 -

REMINGTON ARMS COMPANY, INC. Ilion Research Division

April 28,

1959

cc: S.M. Alvis

D.E. Miller

R.A. Williamson

H.J. Hackman V.G. DeReus

R.B. Hurley W.E. Leek

W. A. BEST

244 CALIBER - PILOT LINE TEST

Ten of the subject guns were withdrawn for test on 4/20/59 and completed on 4/21/59.

Procedure

- All ten guns were fired three 5-shot groups for accuracy, using one shooter, 20% scope, and the 90 gr. bullet, from the 100 yd. gallery range.
- All guns were then field tested 40 rds. each (20 rds. of 90 gr. and 20 rds. of 75 gr. shells). Four shooters were used and all firing completed at Kay Bros. shooting pit. All guns were also tested for unloading live ammunition.

Conclusions

Punctioning

All guns functioned satisfactorily in live round shooting with no malfunctions occurring.

Six of the ten, the extractors dropped the shell in unloading live ammunition. This is not considered serious since the shooter can cant the gun and the round will fall out. However, it is believed that this should be checked further.

Accuracy Test

With the exception of one gun (#711636) all others are near the 2" gallery specs. or better. The one mentioned, not qualifying, appears to be throwing a flyer.

Accuracy results are attached.

CJT:T

C. Heriault Supervisor - Testing Unit

ACCURACY TEST - Model 725 - 244 Caliber April 20-21, 1959

| 3 - 5-shot groups 20X Scope Inside to Inside Meas. | | | | 100 yd. Indoor Range 90 gr. S.P. Bullet |
|--|-------|----------------|-------------------------|--|
| Gun No. | | Group Size | | Average |
| 1. 71 | 1478 | 1. 2. 3. | 1.3 " 1.6 " 2.55" | 1.81" |
| 2. 71 | 1434 | 1. 2. 3. | 2.5 " 2.1 " 1.6 " | 2.07" |
| 3. 71 | 1668 | 1. 2. 3. | 1.2 " 1.85" 2.7 " | 1.91" |
| 4. 71 | 11571 | 1. 2. 3. | 1.9 " 1.8 " 1.0 " | 1.56" |
| 5. 71 | 1629 | 1. 2. 3. | 2.2 " 2.7 " 1.2 " | 2.03 ⁿ |
| 6. 71 | 1632 | 1. 2. 3. | 1.15" 1.1 " 1.4 " | 1.21" |
| 7. 71 | 1636 | 1. 2. 3. | 3.4 " 2.5 " 1.8 " | 2.56" |
| 8. 71 | 1615 | 1. 2. 3. | 2.0 " 2.1 " 1.5 " | 1.86" |
| 9. 71 | | 1. 2. 3. | 1.3 " | 1.16" |
| 10. 71 | 1585 | 1. 2. 3. | 2.05" 1.85" 2.1 " | 2.00" |
| CJT:T 4-28-59 | | | | |