

CAL. 30.06 SPRG.

REMINGTON M/710 TRIAL and PILOT DAILY TEST DATA SHEET

PROJECT #241095
TLW0300

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	TOTAL RDS.
				RDS. FIRED	
SW/JW/BL	11-4-00	PROOF STAMP + MAGNATELUX STAMP			
SW/JW/BL	11-4-00	HEAD SPACE	min + .002		
SW/JW/BL	11-4-00	Load Safety Function test	Remington Ammo R30064 (Shot 10 Rounds)	10	10
SW/JW/BL	11-4-00	HEAD SPACE	min + .002		
Vespe/BL	11-5-00	POI Relative To POA		5	15
JA/BL	11-5-00	Trigger Pulls	(1) 4.5 (2) 4.25 (3) 4.25 AVERAGE 4.33		
JA/BL	11-5-00	Indents	(1) .018 (2) .018 (3) .018 AVERAGE .018		
JA/BL	11-5-00	Measurements	Sear Trigger Engagement (1) .0259 (2) .0265 (3) .0267 Average .0263		
			Sear Lift (1) .0152 (2) .0147 (3) .0145 Average .0148		
SW	11-5-00	Bolt Stop Function Test	OK Locked position / Unlocked position Barre Hand OK Closed Hand OK		
PCR	11-6-00	Returned to	Manifold to show trigger in Normal position location relative to Trigger guard.		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

Forms

BARBER - 5.22.06r0000974

1

ET06805

Confidential - Subject 5.22.061006974 Order

Subject: 5.22 Protective Order
BARBER - 5.22.06r0006974

Williams v. Remington