

GUN # A-14

SERIAL # 7100 1004

CAL. 30.06 SPRG.

REMINGTON M/710

TRIAL and PILOT

DAILY TEST DATA SHEET

PROJECT #241095

TLW0300

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
SW/JW/BL	11-4-00	PROOF STAMP & MAGNAFLUX STAMP ✓			
SW/JW/BL	11-4-00	Headspace min + .003			
SW/JW/BL	11-4-00	Trigger Pulls (1) 4.75 (2) 3.75 (3) 4.25 AVERAGE 4.25			
SW/JW/BL	11-4-00	Indents (1) .018 (2) .018 (3) .018 AVERAGE .018			
SW/JW/BL	11-4-00	Bolt Stop function test Locked position / unlocked			
		Bare hand OK Gloved Hand OK			
SW/PA	11-5-00	10 Rd Function Test	Remington Ammo R30064		
		Bolt fired to close on live round (PR)			
		Round #7, did not fire using lanyard,			
		waited 30 seconds, entered blowup room,			
		removed round & inspected primer, visible			
		mark on primer from firing pin, closed			
		bolt with no round in chamber, pulled			
		Trigger by hand, no Trigger movement was			
		detected, cycled several times by hand			
		and Trigger functioned normal, continued			
		lanyard test & dropped unfired round.			
		Round #10 Same as #7, did not fire, primer			
		has been marked by firing pin.		8	8
		Gun OUT OF TEST (PKR)			

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

Forms

ET06807