

REMINGTON ARMS COMPANY, INC.
ENGINEERING DEPARTMENT CONFIRMATION SHEET

AUDIT TEST
M600 6.5MM. MAG.
PARAMETERS AS RECEIVED

65

3-17

67

TEST FUNCTION	GUN NO. 1	GUN NO. 2	GUN NO. 3	GUN NO. 4	GUN NO. 5	GUN NO. 6	GUN NO. 7	GUN NO. 8	GUN NO. 9	GUN NO. 10	DESIGN SPECS.
GUN SERIAL NUMBER	73969	75134	73284	75662	73783	74204	74311	70850	73462	75078	
HEADSPACE CHECK	OK	OK	OK	OK	OK	OK	OK	OK	OK	OK	MIN. 60 MAX. NO 60
FIRING PIN INVENT - IN.	.01925	.0203	.01915	.0185	.01775	.01945	.01705	.01925	.01935	.01925	.018 - .026
TRIGGER PULL LBS.	4.775	4.45	5.40	5.775	5.20	5.20	6.9	5.35	6.725	4.575	4 - 6
FIRING PIN PROTRUSION IN	.055	.060	.056	.056	.056		.058			.061	.045 - .075
COCKED BOLT LIFT. LBS.	5.0	4.8	4.5	4.8	4.1	4.0	5.0	5.1	5.0	5.0	N.A.
DRY FIRED BOLT LIFT LBS.	11.1	8.0	8.0	7.9	8.0	10.1	8.0	8.0	8.0	8.4	N.A.
GROUP SIZE MACHINE REST IN.	3.28	2.18	3.15		2.96	4.01	3.28	2.96	3.55	4.4	3.50
HORIZ. SPREAD MACHINE REST IN.	2.83	1.57	1.53		1.43	2.17	1.9	2.7	2.27	2.2	3" left or right
VERT. SPREAD MACHINE REST IN.	1.63	1.58	3.03		2.7	3.58	2.77	2.3	2.55	4.01	2" low 4" high
GROUP SIZE Shoulder shot. IN		2.62			2.40	3.00		3.40	1.65	2.27	3.50
HORIZ. SPREAD Shoulder shot IN.		2.13			2.27	2.26		2.75	1.25	1.87	3" left or right
VERT. SPREAD Shoulder shot IN.		1.92			.65	2.45		2.56	1.55	1.83	2" low 4" high
RE-TEST MACHINE-REST GROUP SIZE, HORIZ. SPREAD						OK - WITHIN STDS.				OK - WITHIN STDS.	
GUN FAILURES			BROKE BOLT HANDLE								