

Discontinued for 1969

MODEL 600		308 Win.	5MM Rem.	222 Rem.	243 Win.	223 Rem.
ACCURACY						(Export only)
Range	100 yards					
Point of Aim	6 o'clock on target.					
Center of Impact	Not more than 2 inches below or 4 inches above of 3 inches either side of point of aim.					
Group Size (E.S.)	5 shots in: 3 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"	2 1/2"
	4 shots in: 3"			XX		
Ammunition	180 gr. PSP	100 gr. PSP	50 gr. SP	XX	100 gr. PSP	55 gr. SP
ACTION						
	Bolt action, hand operated. Removable bolt. Solid frame with takedown stock. Bolt cocks as handle is raised. Rifle cocks as bolt handle is lowered to lock action closed. Extracts and ejects as bolt is "opened". Direct action trigger. 2 stop safety - Forward to FIRE position - rearward to ON SAFE stop position.					
	Action must feed, fire, extract and eject (include extraction and ejection without firing) satisfactorily with all varieties of ammunition listed as standard (for tabulated callipers) in Technical Committee Manual of the Sporting Arms and Ammunition Manufacturers' Institute (SAAMI).					
ANNOUNCEMENT						
Jan.	1964	1964	1964			
June		1964			1965	1965
Warehouse Date						
DISCONTINUED						
Jan.						
June			1967			

REVISED 4-1-66 3-22-67

REMINGTON STANDARDS - ARMS

SHEET 2

MODEL 600	308 Win.	6MM Rem.	222 Rem.	243 Win.	223 Rem. (Export only)
BARREL	Round tapered to breech and crowned at muzzle. Black color, medium lustre. Remington specification alloy steel. Steel barrel studs (6) for rib and sight attachment.				
Bedding	No requirement.				
Barrel Bracket	Elevated type.				
Length (Nominal)	18 1/2"				
Diameter (O.D.)	Regular size.				
Bore (in.)	.300 min. .302 max.	.237 min. .238 max.	.219 min. .220 max.	.237 min. .238 max.	.219 min. .220 max.
Groove (in.) (6)	.308 min. .310 max.	.243 min. .244 max.	.2240 min. .2250 max.	.243 min. .244 max.	.224 min. .225 max.
Twist (R.H.)					
1 Turn in	10 inches	9 inches	14 inches	9 inches	12 inches
Markings	See MARKINGS - Barrel				
BARREL RIB	Black Delrin. Ventilated type attached to barrel stud with screws.			Matted between sight positions.	
BOLT (Final Assembly)	Includes Bolt Assembly. Firing Pin Assembly.				
Bolt Body	Bright steel				
Bolt Plug	Black color.				
Bolt Handle	Bright steel color. Forward "S" shape with oval "bolt ball". Serrated on bottom of half ball.				
Firing Pin Head	Black color.				
Markings Export	Serial number on bottom of bolt. See MARKINGS - Bolt. Use "shrouded" bolt plug - special design.				
BOLT STOP	Located in left rear of "bolt track" in receiver. Use narrow tool to push down for release.				

REMINGTON STANDARDS - ARMS

REVISED 3-22-64 7-1-65

223 Rem.
(Export only)

MODEL	600	308 W/in.	6MM Rem.	222 Rem.	243 W/in.	223 Rem. (Export only)
BUTT PLATE	Black plastic					
EJECTOR	Plunger type - spring loaded and pin assembled in bolt head.					
EXTRACTOR	Riveted to bolt.					
PRING PIN	Spring retracted in bolt.					
Protrusion	.045 min. - .075 max.					
Indent	.018 min. - .026 max. (using copper crusher)					
GUN - Length (Overall)	37 1/4" (Nominal)					
- Weight	5 1/2 lbs. (Nominal)					
MAGAZINE	Fixed - top loading					
Capacity	4			5	4	5
Follower	Bright plate.			Yes	No	Yes
Spacer	No					

MODEL 500		308 W/in.	6MM Rem.	222 Rem.	243 W/in.	223 Rem.
MARKINGS		All marking visible unless specified otherwise.				(Export only)
Barrel		Dwg. B-15729				
Assembly		Left rear				
Remington Name		Left side				
Rem. Address		Left side				
Caliber		Left rear				
Code (Mfg. Date)		Left rear				
Patent Numbers		Below Remington name (if any)				
Proof (REP)		Right rear				
Test		Right rear				
Other:						
Magnaflux		Right rear (to rear of (REP) marking).				
Receiver						
Grade		Dwg. B-15432)				
Remington Script		None				
Model Number		Left center				
Serial Number		Below script (Rem.)				
Export:		Left front				
		To Australia: Mark "S" and "P" on receiver adjacent to respective SAFE and FIRE stop positions of safety.				
Bolt						
Magnaflux		(Prick-punch mark) Ref				
Bolt head braze		Right lug (center)				
Bolt handle braze		Left lug (center)				
Proof		Rear handle (center)				
		Bottom handle (center)				
METAL FINISH						
		Black color				
		medium luster on all exposed parts except as otherwise tabulated.				
PATENT NUMBERS						
		None				

SHEET 5

REVISION 3P-22-67 7-1-65 REMINGTON STANDARDS - ARMS

MODEL 600		308 Win.	6MM Rem.	222 Rem.	243 Win.	223 Rem.
PACKAGING	Full length.	Exposed metal parts coated with rust preventive.			Bolt in rifle.	(Export only)
Accessories	Rear sight wrench supplied.					
Literature	Instruction Folder - Parts List RD 5473					
Single Shipper	Single piece corrugated sheet. Integral folds for rifle support.				Marbled color with brown and	
Multiple Shipper	Black artwork (Deer and Bear). Lid taped to close.					
Label	Sleeve or full carton of corrugated material.					
Markings	Green and white, model, serial number, caliber, packers code on label.					
	Name and address of addressee, with copy of shipping ticket, return address.					
Shipping Weight						
1 Gun	8 lbs.					
2 Guns	16 lbs.					
3 Guns	23 lbs.					
5 Guns	38 lbs.					
Export	Same as domestic except Legal or actual weight on label.					
PROOF TEST (REP)	Fire one (1) standard proof cartridge in each gun.				For location of marking (REP) see MARKINGS - Bar	
RECEIVER	Cylindrical alloy steel. black color, medium lustre. Screw fitted to barrel and barrel bracket (gold frame).					
Sighting	Drilled and tapped (5 holes) for receiver sight and telescope mount. Fitted with receiver plug screw					
Gas Escape	One (1) hole - right side					
Length	Standard					
Markings	See MARKINGS - Receiver.					

MODEL	500	308 Win.	6MM Rem.	222 Rem.	243 Win.	223 Rem.
SAFETY	2-stop position, forward and back-thumb operated.	Serrated black surface.				
Location	Right rear of receiver.					
Fire Position	Forward stop.					
Safe Position	Rear stop. (Bolt handle locks down - action closed).					
SERIAL NUMBER	(Start 1000)					
Location (1)	See MARKING - Receiver.					
(2)	See MARKING - Bolt.					
SLING STRAP	As accessory at extra cost.					
Description	7/8" QD type same as used on M/700. Leather material.					
SIGHTS						
Front	Metal material. Black color.					
	Fixed (no adjustment). Blade shaped ramp. Brass head. Attached on rib to barrel studs with two (2) screws.					
Rear	Sliding adjustment for windage and elevation.					
Eye-piece	Allen-head screw for elevation adjustment. "U" notch.					
Leaf	Allen-head screw for windage adjustment. Scaled markings.					
Base	Attached to barrel with two (2) screws.					
Wrench	Allen-head type. Supplied with each gun.					

[illegible]