

REMINGTON ARMS COMPANY, INC.

INTER-DEPARTMENTAL CORRESPONDENCE



Bridgeport, Connecticut
July 14, 1967

TO: F E MORGAN

FROM: G G D ROCKWELL

SUBJECT: TEST REPORT ON MODEL 660

On July 10th, I tested sample Model 660, Serial No. 89890. Temperature was approximately 80°, humidity was high; ammunition was supplied with test rifle and was factory loaded, Index 8308, which is 308 Win., 180 Grain, pointed, soft point, core lakt.

As can be noted on the rifle, there has been some sort of bleeding notable at the junction of a white line spacer on the fore-end tip and the wooden stock. This would not be desirable from a customer point of view. Also, the checkering impression on the left side of the fore-end is quite light, and the stock has warped considerably toward the right in the fore-end area, thereby making the barrel-to-wood fit less than acceptable.

The entire forty rounds were fired. The bolt handle is not as easy to operate as on some other rifles, and when hands are sweaty it becomes slippery. As you can see from the targets, the sights were set to shoot a little to the left. The ammunition fit smoothly. Ammunition cases and targets are submitted herewith.

The gun was a joy to shoot. The heavier and longer barrel makes sighting easier and recoil less objectionable. Rifle shoulders well and trigger is the best I have ever felt. Action works smoothly and lockup is solid. Firing pin blows wherein exact center of primer and impression was good. Sights were highly visible.

Gun is being returned to you with this report.

George G.D. Rockwell /m

GGDR.RWP