

107-18 REV.
20

M/700

PART: RECEIVER	PART No. See Below M/700-660-40X-KP100
----------------	---

MATERIAL PROCUREMENT-RAW MATERIAL

Detailed Description		REV. NO.	DATE
PIECES REQUIRED PER ASSEMBLY: 1		9	12-1-56
MATERIAL:	AISI-4137 Modified Alloy Steel (S-.06/.10)	10	6/28/67
SIZE:	1-29/64 Dia. ±.014 x 12'3" long. 10% random shorts acceptable down to 5'5" lengths in multiples of 9" plus 2" per bar.	11	12/28/67
CONDITION:	Hot Rolled, Annealed Mechanically Descaled, Oiled and Machine Straightened		
WEIGHT PER 100:	Long Receivers - 451 #/100 Short Receivers - 416 #/100 600 660 - 360 #/100		
LOADING - CAR AND TRUCK SHIPMENTS:	Maximum weight of lifts, 10,000#. Lifts must be separated by suitable blocks for overhead crane unloading.		
USES OF PART:	M/700 - 26575, 26576, 16367, 15310, 26577 M/600 - 15406, 15787, M/40X - 15310 M/KP-100 - 15476 M/660 - 29885, 29886		
IDENTIFICATION OF MATERIAL:	Routing Ticket to be marked Mat. Spec. No. 4137 Mod.		
REMARKS:	* The following should be noted on purchase orders for above material. "The annealed micro structure should show a minimum of 25% pearlite and have a hardness of <u>210/230</u> Brinell." <i>Course again 180/190</i>		
AUG 16 1970			
COMPILED BY: E. R. Carr DATE: 12-1-66 76420 ✓		APPROVAL & DATE: <i>[Signature]</i> 12/1/66	
265036		REMINGTON ARMS COMPANY, INC., ILION, N. Y.	

M. H. SULLIVAN, INC. 265725