

Rev. 1-14-80

REVISED 3-12-73

REMINGTON STANDARDS - ARMS

SHEET 8 of 8

MODEL 700	1974 Version	ADL Grade		BDL Grade	
STOCK (Continued)					
Dimensions (Nominal - 30-06)		See Below		See ADL Grade	
Drop at Heel (from Q of barrel)		1 5/16"		"	
Drop at Comb & Monte Carlo (From Q of bbl.)		1 1/16"		"	
Length of Pull		13 3/8"		"	
Length of Grip		3 3/8"		"	
Pitch (from Q of barrel)		2 7/8"		"	
Fore-end Cap (black plastic)		No		Yes	
Spacer (white plastic)		--		Yes	
Grip Cap (black plastic)		No		Yes	
Spacer (white plastic)		--		Yes	
Swivels (2) 7/8" Q. D. (Quick Detachable)		No		Yes	
(1) Weight (7mm-08 Varmint)				2 lbs. - 7oz. Max.	
TRIGGER					
Pull (Wt.)	Direct action black metal, wide serrated finger piece, full radius.				
Engagement	3 lbs. Min. - 5 lbs. Max. (with wt. sealed at factory).				
	Adjustment sealed at factory				
TRIGGER GUARD					
Type	Aluminum alloy, black color.	Anodized - High Lustre			
		Short		Long (with floor plate)	
WEIGHT					
	(See Gun Length & Weight)				
(1) Added					

REVISED 3-12-73

SHEET 7 of 8

REMINGTON STANDARDS - ARMS

MODEL 700		1974 Version	ADL Grade		BDL Grade	
RECOIL PAD						
Calibers:		Black Color				
(2) Markings:		All Magnum Grades only.				
Spacer		"Remington" on back surface See Logo B2 for Size				
		White plastic				
SAFETY						
Location		2 stop position, thumb operated - forward and back. Corrugated, black surface.				
"FIRE" position		Right rear of Receiver				
"SAFE" Position		Forward stop position. Marked "F" on receiver.				
		Rearward stop position (Bolt lock position also). Marked "S" on receiver				
SERIAL NUMBER						
Location		(Start 6,200,000 Last No. 6,899,999 Ref. See Marking Dwg. C-1536Q)				
		See MARKINGS - Receiver				
		See BOLT - Markings				
		(Last four (4) numbers only)				
SLING STRAP						
Type - 7/8"		Leather, one piece - purchased. Accessory			St. Equipment	
SLING SWIVEL 7/8"						
Q. P.		See STOCK			Standard Equipment	
SIGHTS						
Front		Metal, black color. (Removable).				
Rear (1)		Brass face held (dovetail) with screw (2) fit ramp.				
		Open, U-Notch - adjustable for windage and elevation. Sliding ramp for elevation				
STOCK (Assembly)						
Finish		American walnut, reddish filler, Monte Carlo with cheek piece. Pistol grip with comb cuts and checkered (Custom). See action: Long action, short action caliber use				
Butt Plate		See Butt Plate			RK-W	
Spacer (White Plastic)						
Recoil Pad		(MAGNUM caliber use only)				
Checking						
Recoil Pad Spacer (White Plastic)					D-90976	
					D-91001	
(1) REF: Op. Comm. meeting min. No. 9, June 1972, approving release to production.						
(2) See Memo J. H. Lewis to J. F. Finnegan dated 8-24-73						

MODEL 700 1974 Version		ADL Grade		BDL Grade	
PACKING		Full length in single wall, inner rifle carton. Bplt removed and packed separately in same carton. Exposed metal parts coated with rust preventive.			
Inner Carton		One piece folding, corrugated fiber board.			
Literature Markings		Gun Owner's Guide - Form No. 5461 in carton. Misc. sale items if available. Printed label giving manufacturer, model name and/or number, caliber, serial number and packing code, sales number.			
Outer Carton		1, 2, 3 or 5 inner carton capacity. Corrugated carton of greater strength. Copy of regular Remington shipping ticket with, complete information. Name, address of Purchases with purchaser's order number.			
Shipping Weight					
1 gun			10 lbs.		
2 guns			19 lbs.		
3 guns			27 lbs.		
5 guns			46 lbs.		
Export		Packaging same as domestic but with "legal" or actual weight recorded on label.			
PATENT NO's		2,473,373 - 2,514,981 - 2,585,195			
PROOF TEST (REP)		Fire one (1) - standard proof cartridge in each rifle. For location of marking (REP), see MARKINGS - Barrel.			
RECEIVER		Cylindrical, alloy steel, black medium luster.			
Action Lengths		See Gun Length and Weights			
Finish		Medium Luster.			
Gas Escape		(1) Right Hand Side			
Markings		See Markings - Receiver			
Sighting Feature		(6 holes) Drilled and tapped for popular scope mount and receiver sight. Anti-bird design.			

SHEET 5 of 8