

3-5-72

REVISED 11-25-70

REMINGTON STANDARDS - ARMS

RIFLING INDEX

SHEET 1 of 1

MODEL 700 Rifle	C. F. Rifle	TWIST R. H.	GROOVE No.	BORE (LAND) DIA.	WIDTH	GROOVE DIA.	WIDTH
*222 Rem.		14"	6	.219"	.035"	.224"	.080"
*25-06 Rem.		10"	6	.250"	.036"	.2568"	.095"
*22-250 Rem.		14"	6	.219"	.035"	.224"	.080"
223 Rem (Varmint only)		12"	6	.219"	.035"	.224"	.080"
*6MM Rem.		9 1/8"	6	.237"	.032"	.243"	.090"
*243 Win.		9 1/8"	6	.237"	.032"	.243"	.090"
270 Win.		10"	6	.270"	.036"	.277"	.105"
30-06 Spgfd.		10"	6	.300"	.042"	.308"	.115"
308 Win.		10"	6	.300"	.042"	.308"	.115"
7MM Rem. Mag.		9 1/4"	6	.277"	.035"	.284"	.110"
264 Win. Mag.		9"	6	.256"	.039"	.264"	.095"
300 Win. Mag.		10"	6	.300"	.042"	.308"	.115"
375 H & H Mag.		12"	6	.366"	.077"	.376"	.115"
458 Win. Mag.		14"	6	.450"	.086"	.458"	.150"
6.5mm Rem. Mag.		9"	6	.256"	.039"	.264"	.095"
350 Rem. Mag.		16"	6	.349"	.053"	.357"	.130"
17 Rem.		9"	6	.168"	.026"	.172"	.063"
* Also Varmint use.							