

MODEL	700	ADL Grade		BDL Grade	
ACCURACY		Use open sights, fore-end and elbow rest. Use third notch on sight step.			
Test Ammunition:		See Accuracy Index.			
Group Size:		See Accuracy Index.			
Center of Impact:		Not more than 2 inches below, or 4 inches above, or 3 inches either side of point of aim.			
Point of Aim:		6 o'clock on target.			
Range:		100 yds.			
ACTION		Bolt action, center fire, hand operated repeater. Solid frame with take-down stock.			
		Fixed magazine. Bolt cocks as handle lifts. Rifle cocks as bolt handle is lowered to lock action closed.			
		Extracts and ejects as bolt is "opened". Direct action trigger. 2 stop safety. FIRE position - forward			
		SAFE position - rearward. Rear position of safety locks bolt closed.			
Short Action Calibers		222, 308	222, 308		
		243, 6mm	243, 6mm		
		22-250	22-250, 17 Rem.		
			6.5, 350 Mag.		
Long Action Calibers:		30-06, 25-06	30-06, 25-06		
		270, 7mm	270, 7mm		
			264, 300 Mag.		
		Action must feed, fire, extract and eject (include extraction and ejection without firing),			
		satisfactorily with all varieties of ammunition listed as standard for listed calibers in Technical			
		Committee Manual of the Sporting Arms and Ammunition Manufacturers' Institute (SAAMI).			

MODEL 700		ADL Grade		BDL Grade	
ANNOUNCEMENT					
30-06	1962				
270 Win	1962				
222 Rem.	1962				
7mm Rem. Mag	1962				
264 Win. Mag.	1962				
300 Win. Mag.	1964				
308 Win.	1962				
243 Win.	1962				
25-06 Rem.	1970				
6mm Rem.	1963				
22-250 Rem.	1965				
17 Rem.	1971				
6.5 Rem. Mag.	1969				
350 Rem. Mag.	1969				
BARREL	Round, tapered to breech, crowned, Black color, Medium Inure.				
Material:	Remington specified alloy steel, Stainless steel for 17 Rem. Only.				
Bore-Groove:	See Rifling Index.				
Optional Barrel:					
Markings:	See Marking - Barrel.				
BOLT ASSEMBLY:	3 piece brazed assembly - Bolt body, Bolt head, Bolt handle. Includes Firing Pin Assembly.				
Bolt Plug:	Cover firing pin head. Black color				
Bolt Handle:	Swept back oval shape ball. Checker on upper and lower face of ball. Black color				
Bolt Body:	Bright Steel - damascene finish.				
Bolt Head	Black color.				
Markings:	See Marking - Bolt				
Size:					
Small	222, 17 Rem.				
Short Std.	243, 6mm, 308, 22-250				
Standard	30-06, 270, 45-06				
Short Magnum	6.5, 350, Mag.				
Magnum	7mm, 264, 350 Mag.				

MODEL	700	ADL Grade	BDL Grade
BOLT RELEASE		Located to front of trigger.	Black color.
BUTT PLATE		Screw (2) fitted Black plastic, corrugated surface.	
Caliber use:		30-06, 25-06, 222, 22-250, 270, 243, 308, 6mm, 17 Rem. (See Recoil Pad for Magnum calibers).	
EJECTOR		Plunger Type, spring loaded, pin assembled to bolt head.	
EXTRACTOR		Circular, clip type, riveted inside bolt head.	
FIRING PIN		Spring retracted in bolt.	
Indent		.018" Min. - .026" Max. (use copper crusher)	
Protrusion		.045" Min. - .075" Max.	
FLOOR PLATE		Black metal. Latch in trigger guard.	No
Use			Yes
FORE-END (Cap)		Black plastic - bonded to stock.	No
Use			Yes
Spacer			White Plastic
GRIP CAP		Black plastic - bonded to stock.	No
Use			Yes
Spacer			White plastic

[illegible]

MODEL 700		ADL Grade		BDL Grade	
MARKINGS - Barrel (Dwg. C-15360)					
Assembly	Left Rear				
Caliber	Left Rear of Remington name.				
Code (Mfg. Date)	Left Rear				
Inspection	Left Rear				
Patent Numbers	Below Remington address.				
Remington Address	Left Side				
Target	Right Rear.				
Test	Right Rear				
Magnaflux	Right Rear				
Other	---				
MARKINGS - Bolt (Prick-punch mark)					
Bolt Handle Braze	Rear Handle (Center)				
Bolt Head Braze	Left Lug (Center)				
Magnaflux	Right Lug (Center)				
Proof	Bottom Handle (Center)				
Serial Number (1)	Underside (Rear)		Last four (4) numbers only.		
MARKINGS - Receiver (Dwg. C-15360)					
Grade	None				
Model Number	Below Remington Script				
Model Script	None				
Remington Script	Left Side				
Serial Number	Left Side, Front				
Other	Mark "S" and "F" on receiver below and above resp. SAFE and FIRE stop positions of safety.				

REVISED 5-9-72

REMINGTON STANDARDS - ARMS

SHEET 7 of 8

MODEL 700		ADL Grade		BDL Grade	
RECOIL PAD					
Calibers:	All Magnum	Grades, only	S. d. Equipment		
SAFETY					
Location	2 stop position, thumb operated		Right rear of Receiver.		
"FIRE" Position	Forward stop position, Marked "F" on receiver.				
"SAFE" Position	Rearward stop position (blow lock position all 10). Marked "S" on receiver.				
SERIAL NUMBER					
Location	(Start 6,200,000 - Last No. 6,999,999 Ref" See Marking Dwg. C-15360)				
	See MARKINGS - Receiver				
	See BOLT - Markings				
	(Last four (4) numbers only)				
SLING STRAP					
Type - 7/8"	Leather, one piece - purchased		Accessory		St. Equip.
SLING SWIVEL					
	See STOCK		Accessory		Standard Equip.
			(added cost)		
SIGHTS					
Front	Metal, black color. (Removable)				
Rear	Brass face head (dovetail) with screw (2) fit ramp.				
	Open, U-Notch (with adjustable step).				
STOCK (Assembly)					
Finish	American walnut, reddish filler, Monte Carlo with cheek cuts				
Butt Plate	and checkered (Custom). See action, long action caliber use.				
Spacer (white plastic)	RK-W				
	See Butt Plate				
	No				Yes
Recoil Pad:					
Checker (die impressed)	(MAGNUM caliber use only)				
Dimensions (Nominal - 30-06)					
Drop at Heel (from C of barrel)	D-14698				D-14697
Drop at Comb & Monte Carlo (from C of bbl.)	See Below				See ADL Grade
Length of Pull	15/16"				"
Length of Grip	11/16"				"
Pitch (from C of barrel)	13 3/8"				"
	5 3/8"				"
	2 7/8"				"

MODEL 700		ADL Grade		BDL Grade	
STOCK (Continued)					
Fore-End Cap (black plastic) Spacer (white plastic)	No —			Yes Yes	
Grip Cap (black plastic) Spacer (white plastic)	No —			Yes Yes	
Swivels (2) 7/8" Q.D. (Quick Detachable)	No			Yes	
TRIGGER					
Pull (Wt.)	Direct action, black metal.	Wide serrated finger piece, full radius.			
Engagement	3 lbs. Min. - 5 lbs. Max. (with wt. sealed at factory).				
	Adjustment sealed at factory.				
TRIGGER GUARD					
Type	Aluminum alloy, black color	Anodized — High Lustre		Long (with floor plate)	
		Short			
WEIGHT	(See Gun Length & Weight)				