

TEST FUNCTION	ONE	TWO	THREE	FOUR	FIVE	SIX	SEVEN	EIGHT
SERIAL NUMBER	6658188	6658215	6658320	6658138	6658211	6658329	6658086	6658222
HEADSPACE - (MIN. +)	.001	.002	.001	.001	.000	.002	.003	.002
TRIGGER PULL - LBS.	3.75	4.25	3.75	3.25	4.50	4.00	3.75	3.75
FIRING PIN INDENT-IN.	.0175	.0165	.0175	.0180	.0170	.0195	.0190	.0175
GUN WEIGHT - LBS.	7-15	7-13	7-14	7-12	7-15	7-11	7-12	7-14
GUN LENGTH - IN.	44 1/2	44 3/8	44 3/8	44 3/8	44 3/8	44 3/8	44 3/8	44 3/8
AS REC'D REAR SIGHT	44 NOTCH	44 NOTCH	44 NOTCH	44 NOTCH	44 NOTCH	44 NOTCH	44 NOTCH	44 NOTCH
AS REC'D P.O.I.	0-0	0-0	0-3.5R	2.5H-0	2.0L-0	3.0H-3.0R	0-0	1.5L-1.75L
LOWEST - P.O.I.	6.0L	10.0L	9.0L	2.5L	7.0L	1.0L	7.0L	6.0L
HIGHEST - P.O.I.	18.0H	17.0H	12.0H	21.0H	15.5H	18.0H	18.0H	17.0H
GROUP SIZE - 3XSS NOTATION	2.01	1.88	1.91	—	—	—	1.98	—
HORIZONTAL	1.28	1.81	1.68	—	—	—	1.69	—
VERTICAL	1.75	0.92	0.87	—	—	—	1.29	—
SCOPE ADJ. - HIGHEST	—	—	—	—	—	—	49.0H	—
SCOPE ADJ. - LOWEST	—	—	—	—	—	—	13.5L	—
FIELD TEST ROUNDS	60	60	60	60	60	60	60	60
FIELD TEST MAL FEED	0	0	0	0	0	1047 OF 1088	21 DE.	0
JACK ENOUGH	250	—	—	250	—	—	—	500
HEADSPACE - MIN +	.001	—	—	.001	—	—	—	.002

[illegible]