

DON'T SAY IT—WRITE IT

TO GEORGE MARTIN

SAFETY MALFUNCTIONS

DATE 5-2-75

FROM GENE BULLIS

GALLERY

MODEL	MALFUNCTIONS												TOTAL SAFETY MALFUNCTION BY MODEL			
	FSR			JO			FD			FOS				SWW		
	100	24	73	100	24	73	100	24	73	100	24	73		100	24	73
40							4									4
CP 100							3									3
540																
541								2	1							3
580													1			1
581							3	2	1							6
582																
600	1						10	74	55							140
700	9						7	19	10	1				1		47
788	4						3	9	3	2	9	4	14	95	53	196
EARLY MALF. TOTALS	14						30	106	70	3	9	4	14	97	53	400

TOTAL SAFETY MAL.

MALEFUNCTION MEANINGS

FSR - FIRES WHEN SAFE IS RELEASED - SELF EXPL.

JO - JARS OFF (HAMMER FAILS TO STAY ENGAGED WITH SEAR AND FALLS DOWN WHEN GUN IS JARRED.)

FD - FOLLOWS DOWN (COCKING PIECE FAILS TO PROPERLY ENGAGE WITH SEAR AND FOLLOWS THE COCKING CAM SURFACE OF THE BOLT TO THE FIRED POSITION).

FOS - FIRES ON SAFE (GUN FIRES WITH SAFE IN "ON" POSITION WHEN TRIGGER IS PULLED).

SWW - SAFETY WON'T WORK - SELF EXPL.

* - 1975 DATA FROM DEC. 26, 1974 TO APRIL 29, 1975 ONLY.