

Orig. 12-7-67

REVISED 9-19-75

REMINGTON STANDARDS - ARMS

SHEET 1 of 3

MODEL	700 BDL VARMINT	222 Rem.	223 Rem.	22/250 Rem.	6MM Rem.	243 Win	(2) 25-06 Rem.	308 (3) Win.
Note: All specifications same as M/700 BDL.								
	EXCEPT AS LISTED HEREIN							
ACCURACY (C to C)								
Max. Group Size (5 Shots) E. S.	1.5"	1.5"	1.5"	1.5"	1.5"	1.5"	1.5"	1.5"
All Rifles Must Pass A 5 Shot Specification								
Range	100 yards. Use Accuracy Device.							
Ammunition	(Power-Lock) 50gr.	55gr.		55gr.	80gr.	80gr.	87 gr	150 gr.
	or equiv.							
ACTION								
	Bolt action, handle operated repeater. Solid frame with long stock. Fixed magazine, latched floorplate for bottom unloading, if desired, 2-stop safety, forward to FIRE position rearward to SAFE position.	Short	Short	Short	Short	Short	Long	Short
	Action must feed, fire, extract, eject (include extraction and ejection without firing), satisfactorily with all varieties of ammunition listed as standard for listed calibers in Technical Committee Manual of the Sporting Arms and Ammunition Manufacturers' Institute (SAAMI).							
ANNOUNCEMENT:								
Varmint Model								
Release to Production:	General Management Approval March 16, 1966. See letter V. G. DeReus to Management dated March 18, 1966.							
(2) Ref: Intro. 1971. See OP	Comm Min No 7-1970 Dated 4-3-70.							
(3) Added Ref. Operations	Committee Development Schedule for 1976.							

9-19-75

REVISED 4-6-71

SHEET 2 of 3

REMINGTON STANDARDS - ARMS

MODEL	700 BDL VARMINT	222	223	22-250	6mm	243	25-06	308 (1)
		Rem.	Rem.	Rem.	Rem.	Win.	Rem.	Win.
BARREL (HEAVY):	Round, tapered, colored black. Crowned same as 40X-B. Remington Specification alloy steel.							
Caliber:	See Tabulations.							
Length:	24 inches (all calibers).							
Markings:	Same as M/00							
Sight Holes:	Two (2) one rear taper.							
*Rifling:								
Bore	Min. .219	.219		.219	.237	.237	.250	.300
	Max. .220	.220		.220	.238	.238	.251	.301
Groove	Min. .224	.224		.224	.243	.243	.257	.308
	Max. .2245	.2245		.2245	.2435	.2435	.2575	.309
Twist	(1 Turn) R. H. 14 inches.	12 inches		14 inches	9 1/8 inches	9 1/8 inches	10 inches	12 inches
CAPACITY								
Gun Magazine	6 5	6 5		5 4	5 4	5 4	5 4	5 4
RECEIVER:	Short	Short		Short	Short	Short	Long	Short
*See Model Drawings.								
(1) Added Ref. Operations Committee Development Schedule for 1976								

REMINGTON STANDARDS • ARMS

SHEET 3 of 3

MODEL	700 BDL VARMINT	222 Rem.	223 Rem.	22/250 Rem.	6MM Rem.	243 Win.	25-06 Rem.	308 (1) Win.
GUN LENGTH: (Inches)		43 5/8	43 5/8	43 5/8	43 5/8	43 5/8	44 1/2	43 5/8
SCOPE BASES:	Front & Rear (40X-B type).							
* PACKING: Same as standard (Shipping)								
Weight - 1 Gun	11 lbs.							
Weight - 2 Gun	20 lbs.							
Weight - 3 Gun	30 lbs.							
Weight - 5 Gun	49 lbs.							
STOCK:	Same as M700 BDL Except: modified barrel radius.							
Receiver Cut		Short	Short	Short	Short	Short	Long	Short
WEIGHT:	(with sling) 9 lbs. (dependent upon caliber).							
* Shipping weight revised per W. W. Fenton (warehouse)								
(1) Added. Reference Operations Committed Development Schedule for 1976.								