

Engagement & Lift were measured on the Optical Comparator by the use of the Reflection Unit.

M1600 Australian Gun Evaluation
11-29-77 C.J. Sweet

GUN	CAIBER	Firing Pin Impact Area (in. of 5)	Tracer Pull (in. of 5)	Safe On (in. of 5)	Safe Off (in. of 5)	Engagement (in. of 5)	Lift (in. of 5)
M1600 Serial No. A6315498	308	0223	4.9	3.33	2.66	0.142	0.135
M1600 Serial No. A637413	308	0237	4.75	5.33	4.16	0.205	0.155
M1600 Serial No. A632045	308	0234	4.25	5.5	3.66	0.185	0.125
LOCK TIME M1600 Serial No. A652035	308						
1	33 MSOL						
2	32 MSOL						
3	32 MSOL						
4	32 MSOL						
5	32 MSOL						
6	32 MSOL						
7	32 MSOL						
8	32 MSOL						
9	32 MSOL						
10	32 MSOL						
11	32 MSOL						
12	32 MSOL						
13	32 MSOL						
14	32 MSOL						
15	32 MSOL						
16	32 MSOL						
17	32 MSOL						
18	32 MSOL						
19	32 MSOL						
20	32 MSOL						
21	32 MSOL						
22	32 MSOL						
23	32 MSOL						
24	32 MSOL						
25	32 MSOL						
26	32 MSOL						
27	32 MSOL						
28	32 MSOL						
29	32 MSOL						
30	32 MSOL						
31	32 MSOL						
32	32 MSOL						
33	32 MSOL						
34	32 MSOL						
35	32 MSOL						
36	32 MSOL						
37	32 MSOL						
38	32 MSOL						
39	32 MSOL						
40	32 MSOL						

M1600 Australian Gun Serial No. A652035
Lock Time
0.118 sec

Original Safety Lever for
Measurement



