MODEL M66.12G GAUGE/CAL RIM FIRE (LF) TYPE RIFLE DATE 08/15/7[illegible]

COMPLAINTS RECEIVED (COD.)	%	YEAR OF PRODUCTION 1977	1976	1975	1974	1973	TOP 10 CLASSES
[illegible]	[illegible]	1	13	63	92	132	STOCK
201	28.9	0	7	164	70	2	MAG GUIDE BAR
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	BARREL
72	6.9	0	3	55	12	2	MAGAZINE/OUTER MAG TUBE
62	9.5	0	1	54	0	7	REAR SIGHT
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	TRIGGER HOUSE
31	4.5	0	11	38	2	2	FIRING PIN
14	1.8	0	0	11	2	0	ASSEMBLY - TEST & TARGET
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
11	1.0	[illegible]	3	8	[illegible]	[illegible]	DISCONNECTOR
4[illegible]	53.4	1	53	518	157	21[illegible]	TOTAL ABOVE
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	2	64	329	177	23	GRAND TOTAL
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	44.3	2	28	178	74	10[illegible]	VISUAL (1.)
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]
[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	[illegible]	AVERAGE DEFECT VALUE

R2507563