7-10.05

SAAMI TECHNICAL COMMITTEE MANUAL VOLUME VII, CENTERFIRE RIFLE

ISSUED 10-5-78

REVISED 2-27-79

ACCURACY (Continued)

A trained shooter using an appropriate rest and sights to minimize errors of aim

Max. average of the widest shots measured center-to-center of three 5 shot groups or a statistical equivalent

The accuracy shown is based on the use of ammunition made to SAAMI recommended practices and includes all bullet weights, but not mixed in one group. Each group should be fired with a single lot of ammunition having one bullet weight.

	Bolt, Pump & Single Shot Frame		Lever å Break Open		Autoloading	
Cartridge	100 Yards	100 Meters	100 Yards	100 Meters	100 Yards	100 Meter
	Inches	Centimeters	Inches	Centimeters	Inches	Centimeta
32-20 Win 338 Win Mag 348 Win 35 Rem 350 Rem Mag	4.95 3.85 3.85 3.85 3.50	13.75 10.70 10.70 10.70 9.75	5.40 4.20 4.20 4.20 3.60	15.00 11.65 11.65 11.65 10.00	5.30 4.90 4.90 4.90 4.20	17.50 13.60 13.60 13.60 11.65
351 Win S.L. 358 Win 375 H&H Mag 375 Win 38-40 Win	4.40 3.30 3.85 3.85 4.40	12.20 9.15 10.70 10.70 12.20	4.80 3.60 4.20 4.20 4.80	13.35 10.00 11.65 11.65 13.35	5.60 4.20 4.90 4.90 5.60	15.55 11.65 13.60 13.60 15.55
38-55 Win 44 Rem Mag 44-40 Win 444 Marlin 45-70 Govt	3.85 6.05 3.85 6.05 3.85	10.70 16.80 10.70 16.80 10.70	4.20 6.60 4.20 6.60 4.20	11.65 18.35 11.65 18.35 11.65	4.90 7.70 4.90 7.70 4.90	13.60 21.40 13.60 21.40 13.60
458 Win Mag	5.50	15.30	6.00	16.65	7.00	19.45

All accuracy data and testing is based on the range specified. If the testing facility uses other ranges, proportionate modifications should be made to suit the different range.