

TEST DESCRIPTION

Test

TEST PROCEDURE SHEET

Model XP100Serial No. B7505396Headspace as Received: Min +0Safe - ON - 1. 9-Safe - OFF - 1. 7 $\frac{3}{4}$ Proof: ✓2. 9 $\frac{1}{4}$ 2. 7 $\frac{1}{2}$ Headspace after Proof: Min +.001"3. 9-3. 8-

Firing Pin Indent (in.)

1. .0242. .02453. .025Lift
Bolt ~~Open~~ Force (lbs.)Dry Fired: 1. 7 $\frac{3}{4}$ Cocked: 1. 4 $\frac{1}{2}$ 2. 8 $\frac{1}{2}$ 2. 4 $\frac{3}{4}$ 3. 8 $\frac{3}{4}$ 3. 4 $\frac{1}{2}$

Trigger Pull (lbs.)

1. 2 $\frac{1}{4}$ 2. 2 $\frac{1}{4}$ 3. 2 $\frac{1}{4}$ Lift
Bolt Release Force:

1. _____

2. _____

3. _____

GUN weight 3.69#

STOCK weight .66#

Total Gun Weight: 4.35#Overall Length: 22 $\frac{3}{4}$ "Center of Gravity: 15 $\frac{1}{2}$ from muzzleBore: 308

Choke: _____

Orifice Size: _____

Magazine Spring Force: _____

Primer Marking: _____

Safety Check: C.F.M.

Disconnecter Check: _____

Bolt Closing Velocity: _____

Sear Engagement .0171

Sear Lift .011

Sear Hall position .009

Firing Pin Protrusion: .048"

BBL Length 16"

Tester: Christopher J. Miller SGTDate: 5-31-79REN:CJS:T.
5-7-79