

GUIDED MISSILE LAUNCHING SYSTEM MK 10 MODS 0 THRU 8
PRESERVATION AND DE-PRESERVATION
PROCEDURES AND REQUIREMENTS FOR
TEMPORARY LONG TERM SHUTDOWN

2. MASTER MATERIALS LIST

QTY.

Corrosion Preventative (WS14138) Type I or II As Req'd.
SPRAYON #711 meets the requirements of
WS 14138 and is packaged in the following size
containers:

SPRAYON #711 Type I
16 ounce aerosol spray cans (FSN 1A9150-HDU-1304)

SPRAYON #711 TYPE II
1 gallon (bulk) containers (FSN 1A9150-HDU-1303)
55 gallon (bulk) containers (FSN 1A9150-HDU-1305)

Manufacturers:

SPRAYON Products Inc.
3818 East Coronado St.
Anaheim, California 92306

SPRAYON Products Inc.
26500 Fargo Ave.
Bedford Heights, Ohio 44146

Corrosion Preventative (MIL-C-16173)
Grade 2 (P2) 30 gals.

Silicone Grease (Dow Corning - 55 - 4 eight ounce
pneumatic grease) MIL-G-4343 tubes

Silicone Lubricant (aerosol spray cans) 5 six ounce
"Silicone Slick Spray" cans per RSR

Manufacturer:
Glidden Co.

Barrier Material (MIL-B-121 Type 1 Grade A) As Req'd.