

Start of Test

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

Gun - 1

TEST PROCEDURE SHEET

Model 700 6MM

Serial No. A.6752973



Headspace as Received: _____

* Safe - "ON" - I. 6.50

"OFF" - I. 6.0

Proof: OK

(6.2)

2. 6.0

3. 6.0

(6.0)

2. 6.0

3. 6.0

Headspace after Proof: M+.004

Firing Pin Indent(in.)

Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

1. .024

2. .025

3. .025

Scar lift .0105

Scar engagement .035

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

Bolt Release Force(lbs.)

1. 4.0

2. 3.75

3. 4.0

1. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Described

Safety Check: OK

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

JS
I-12-82