

After 2,000 Rounds

5-12-82

SHOTGUNS, CENTERFIRES, RIFLES (PUMPS & AUTOLOADERS)

Gun - 1

TEST PROCEDURE SHEET

Model 700 ADL 6MM

Serial No. A6752973

Headspace as Received: M + .004

Safe - "ON" - I. 6.0

"OFF" - I. 4.0

Proof: OK

(5.6) 2. 5.5
3. 5.5

(7.3) 2. 7.0
3. 7.0

Headspace after Proof: _____

Bolt Open Force (lbs.)

Firing Pin Indent (in.)

(.0253) 1. .0255
2. .025
3. .0255

Sear lift .0165
Sear Engagement .027

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull (lbs.)

(4.0) 1. 4.0
2. 4.0
3. 4.0

Bolt Release Force (lbs.)

1. _____

2. _____

3. _____

Gun Length: _____

Primer Marking: _____

Gun Weight: _____

Safety Check: OK

Center of Gravity: _____

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

JS

5-12-82