

After 2,500 Rounds

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 RDL

Serial No. 106752973

Headspace as Received: _____

Proof: _____

Headspace after Proof: MIN + .004

Firing Pin Indent(in.)

1. .025
2. .025
3. .026

Trigger Pull(lbs.)

1. 4.50
2. 4.50
3. 4.50

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Safe - "ON" - 1. 7.50

2. 6.00
3. 5.50

"OFF" - 1. 8.00

2. 7.50
3. 7.00

Bolt Open Force(lbs.)

Cocked: 1. _____

2. _____

3. _____

Dry Fired: 1. _____

2. _____

3. _____

Bolt Release Force(lbs.)

1. _____

2. _____

3. _____

Primer Marking: _____

Safety Check: OK

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____