

After 1,000 Rounds

2

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 6MM

Serial No. A 6744896

Headspace as Received: M+.004

Proof: _____

Headspace after Proof: _____

Firing Pin Indent(in.)

0237
1. .0235
2. .0235
3. .024

Trigger Pull(lbs.)

44
1. 4.50
2. 4.50
3. 4.25

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Safe - "ON" - 1. 6.25

6.4
2. 6.50
3. 6.50

"OFF" - 1. 5.25

5.2
2. 5.25
3. 5.0

Bolt Open Force(lbs.)

Cocked: 1. _____

Dry Fired: 1. _____

2. _____

2. _____

3. _____

3. _____

Bolt Release Force(lbs.)

1. _____

2. _____

3. _____

Primer Marking: _____

Safety Check: OK

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

CJS
I-12-82