

After 2,500 Rounds

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700

Serial No. A 6744869

(2)

Headspace as Received: _____

Safe - "ON" - I. 5.50

"OFF" - I. 4.50

Proof: _____

2. 5.50

2. 4.50

Headspace after Proof: MIN + .004

3. 6.50

3. 4.50

Firing Pin Indent(in.)

Bolt Open Force(lbs.)

1. .023

Cocked: I. _____

Dry Fired: I. _____

2. .023

2. _____

2. _____

3. .023

3. _____

3. _____

Trigger Pull(lbs.)

Bolt Release Force(lbs.)

1. 4.50

I. _____

2. 4.50

2. _____

3. 5.00

3. _____

Gun Length: _____

Primer Marking: _____

Gun Weight: _____

Safety Check: OK

Center of Gravity: _____

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

JS
1-12-82