

start of test

3

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 6MM
Serial No. A6744915

Headspace as Received: M 4.004

Safe - "ON" - I. 9.0

"OFF" - I. 6.50

Proof: OK

(9.1) 2. 9.0
3. 9.25

(6.4) 2. 6.50
3. 6.25

Headspace after Proof: _____

Firing Pin Indent(in.)

Bolt Open Force(lbs.)

(.0253) I. .025 Sear lift .015
2. .026 Sear Engagement .025
3. .025

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

Bolt Release Force(lbs.)

(4.7) I. 5.0
2. 4.50
3. 4.25

1. _____

2. _____

3. _____

Gun Length: _____

Primer Marking: _____

Gun Weight: _____

Safety Check: OK

Center of Gravity: _____

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

I-12-82