

after 1,000 rounds

3

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 6MM

Serial No. A6744915

Headspace as Received: M + .004

Safe - "ON" - 1. 10.0

"OFF" - 1. 5.25

Proof: OK

9.7
2. 9.5
3. 9.5

5.7
2. 5.50
3. 6.0

Headspace after Proof: _____

Firing Pin Indent(in.)

0.6
1. .0255
2. .0265
3. .026

Bolt Open Force(lbs.)

Cocked: 1. _____

Dry Fired: 1. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

4.1
1. 4.0
2. 4.0
3. 4.25

Bolt Release Force(lbs.)

1. _____

2. _____

3. _____

Gun Length: _____

Primer Marking: _____

Gun Weight: _____

Safety Check: OK

Center of Gravity: _____

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

EJS
I-12-82