

After 2,500 Rounds

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model

700

Serial No.

AG744915

(3)

Headspace as Received: _____

Safe - "ON" - I. 10.00

"OFF" - I. 5.50

Proof: _____

(9.8) 2. 10.00
3. 9.50

(5.2) 2. 5.00
3. 5.00

Headspace after Proof: Min + .005

Firing Pin Indent(in.)

(.025) 1. .025
2. .025
3. .025

Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

(4.0) 1. 4.00
2. 4.00
3. 4.00

Bolt Release Force(lbs.)

I. _____

2. _____

3. _____

Gun Length: _____

Primer Marking: _____

Gun Weight: _____

Safety Check: O.K.

Center of Gravity: _____

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

JS
I-12-82