

Start of test

4

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 6MM

Serial No. A 6745544

Headspace as Received: M 4.002

Safe - "ON" - I. 8.50

"OFF" - I. 5.50

Proof: OK

(93) 2. 8.50
3. 8.00

(5.4) 2. 5.50
3. 5.25

Headspace after Proof: _____

Firing Pin Indent(in.)

Sear lift .018
Sear Engagement .034

Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

(3.8) I. 3.75
2. 4.00
3. 3.75

Bolt Release Force(lbs.)

I. _____

2. _____

3. _____

Gun Length: _____

Primer Marking: _____

Gun Weight: _____

Safety Check: OK

Center of Gravity: _____

Firing Pin Protrusion: _____

Bore: _____

Choke: _____

Pattern Test (Avg. of 5)

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Group Size: _____

Disconnecter Check: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

I-12-82