

After 2,000 Rounds

5-12-82

Gun 4

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 6MM

Serial No. A 6745544

Headspace as Received: M+.003

Safe - "ON" - I. 7.0

"OFF" - I. 4.5

Proof: OK

7.3 2. 8.0
3. 7.0

4.5 2. 4.5
3. 4.5

Headspace after Proof: _____

Bolt Open Force(lbs.)

Firing Pin Indent(in.)

0.24 1. .022
2. .0215
3. .0215

Sear lift .0155 Cocked: I. _____
2. _____
3. _____
Sear Engagement .035

Dry Fired: I. _____

2. _____

3. _____

Trigger Pull(lbs.)

3.8 1. 3.5
2. 4.0
3. 4.0

Bolt Release Force(lbs.)

1. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: OK

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

CJS
I-12-82