

After 2,500 Rounds

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700

Serial No. N6745544

Headspace as Received: _____

Safe - "ON" - 1. 8.50

"OFF" - 1. 4.50

Proof: _____

8.8 2. 10.50
3. 7.50

43 2. 4.00
3. 4.50

Headspace after Proof: MIN +.003

Firing Pin Indent(in.)

1. .022

2. .022

3. .022

Bolt Open Force(lbs.)

Cocked: 1. _____

Dry Fired: 1. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

1. 4.50

2. 4.00

3. 4.50

Bolt Release Force(lbs.)

1. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: O.K.

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

JS
1-12-82