

Start of test

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 6MM

Serial No. A6747525

5  
Control  
Gun

Headspace as Received: M + .003

Proof: OK

Headspace after Proof:     

Safe - "ON" - I. 5.25

"OFF" - I. 5.50

2. 5.25

3. 5.25

2. 5.25

3. 5.0

Bolt Open Force(lbs.)

Firing Pin Indent(in.)

I. .0255

2. .025

3. .025

Sear lift .019

Sear Engagement .020

Cocked: I.     

2.     

3.     

Dry Fired: I.     

2.     

3.     

Trigger Pull(lbs.)

I. 4.25

2. 4.00

3. 4.50

4.25

Bolt Release Force(lbs.)

I.     

2.     

3.     

~~Gun Length:~~

~~Gun Weight:~~

~~Center of Gravity:~~

~~Bore:~~

~~Choke:~~

~~Orifice Size:~~

~~Bolt Closing Velocity:~~

~~Magazine Spring Force:~~

~~Disconnecter Check:~~

Primer Marking:     

Safety Check: OK

Firing Pin Protrusion:     

Pattern Test (Avg. of 5)

Group Size:     

Horz.:     

Vert.:     

Accuracy (Avg. of 5)

Group Size:     

Horz.:     

Vert.:      P.O.I.:     

• Tester and Date:     

CJS  
I-12-82