

After 2,000 Rounds

5-12-82

Gun 5

Control Gun

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 6MM

Serial No. A6747525

Headspace as Received: M+.003

Safe - "ON" - I. 5.5

"OFF" - I. 5.5

Proof: OK

(5.5)

2. 5.5

3. 5.5

(5.1)

2. 5.0

3. 5.0

Headspace after Proof: _____

Firing Pin Indent(in.)

Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

1. .0255

Sear lift .020

2. _____

2. _____

2. .0255

Sear Engagement .020

3. _____

3. _____

3. .025

Trigger Pull(lbs.)

Bolt Release Force(lbs.)

1. 5.0

I. _____

2. 4.25

2. _____

3. 4.50

3. _____

Gun Length: _____

Primer Marking: _____

Gun Weight: _____

Safety Check: OK

Center of Gravity: _____

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

CJS
I-12-82