

After 2,500 Rounds

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

5-17-82

TEST PROCEDURE SHEET

Model 700

Serial No. A6747525

(5)

Headstace as Received: _____

Safe - "ON" - 1. 5.00

"OFF" - 1. 4.00

Proof: _____

(5.1)

2. 5.00

3. 5.50

(4.8)

2. 6.00

3. 4.50

Headspace after Proof: MIN. 7.003

Firing Pin Indent(in.)

1. 0.025

2. 0.026

3. 0.026

Bolt Open Force(lbs.)

Cocked: 1. _____

Dry Fired: 1. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

1. 5.00

2. 5.50

3. 5.00

Bolt Release Force(lbs.)

1. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: OK

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

I-12-82