11/17/98

M/710 DESIGN & ESTIMATE REVIEW NOTES

8:00 AM: Jeff Swanson

Receiver Insert

- A. Material
 - 1. Questioned Rev. 4 estimate material cost Rev. 5 estimate changed to \$.47
 - Questioned material to be quoted Glass filed Nylon Need specifics
- B. Tooling Goal is to mold part complete w/o secondary op s
 - 1. Quote 2 cavity mold Rev. 5 estimate to reflect cycle time change
 - 2. Can TRT pull adjustment screw holes as designed?
 - change screw holes to open faced to eliminate secondary op's.
 - 3. Need positional tolerance >.003
 - 4. Ø tolerance in question due to shrink, etc.
 - 5. Need to sink threaded insert in tang + Rev. 5 estimate to reflect this
- C. E'town Estimates:
 - Material = 3/lb.
 - Part Volume = 1.8 in^3
 - Cycle Time = 20.7 sec.
 - Part Cost = \$.40 ea.
- D. Mold Flow Analysis Needed to be done to determine accurate cycle time, material, cavitation, etc.

II. Bolt Head

- A. Oper. 80 (Drill Cross Pin Hole) Eliminated, redundant
- B. Oper. 30 (Chamfer Lugs) Eliminated, incorporated into barrel chamber

III. Bolt Plug

- A. Lugs
 - 1. Need to determine if current design is strong enough to support loading
 - 2. Need to determine material to be used Can we flow glass into this area
- B. Mold Cycle Time Rev. 4 estimate high, potential \$ savings
 - 1. Revisited & corrected in Rev. 5 estimate
- IV. Stock Ass y Rev. 5 estimate to reflect stock w/ recoil pad
 - A. Recoil Pad Cost Rev. 5 estimate to reflect M/700 outsource \$
 - B. Stock Cost + Rev. 5 estimate to reflect M/700 outsource \$

