

Start of Test

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

①

TEST PROCEDURE SHEET

Model 700 12mm

Serial No. 1-6752973

Headstace as Received: _____

✓ Safe - "ON" - I. 8.0

"OFF" - I. 7.0

Proof: _____

2. 7.5

2. 7.5

3. 7.5

3. 6.0

Headstace after Proof: MIN 4.004

✓ Firing Pin Indent (in.)

I. 1.025

low

2. 1.025

left .010

3. 1.025

avg .013

Bolt Open Force (lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

✓ Trigger Pull (lbs.)

I. 5.75

2. 5.75

⑤.75

3. 5.75

Bolt Release Force (lbs.)

I. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: _____

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

CJS
I-12-82