

After 1,000 Rounds

(1)

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 6MM

Serial No. A6752973

Headspace as Received: _____

Safe - "ON" - I. 5.50

"OFF" - I. 8.50

Proof: _____

(55) 2. 5.50

(85) 2. 8.50

Headspace after Proof: MIN. + .004

3. 5.50

3. 8.50

Firing Pin Indent(in.)

I. .0255

2. .025

3. .025

Lead
Left .0115
Right .0125

Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

I. 7.00

2. 6.50

3. 6.50

(66)

Bolt Release Force(lbs.)

I. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnector Check: _____

Primer Marking: _____

Safety Check: _____

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

P.O.I.: _____

• Tester and Date: _____

CJS
I-12-82

After 2,000 Rounds
SHOTGUNS, CENTERFIRES, RIFLES (PUMPS & AUTOLOADERS)

(1)

TEST PROCEDURE SHEET

Model 700 6MM

Serial No. A6752973

Headspace as Received: _____

Safe - "ON" - 1. 9.0

"OFF" - 1. 6.5

Proof: _____

(76) 2. 7.0

6.0 2. 5.0

Headspace after Proof: M + .004

3. 7.0

3. 6.5

Firing Pin Indent(in.)

Bolt Open Force(lbs.)

1. .025

Cocked: 1. _____

Dry Fired: 1. _____

2. .025

2. _____

2. _____

3. .025

3. _____

3. _____

*leave
lift .010
eng. .016*

Trigger Pull(lbs.)

Bolt Release Force(lbs.)

1. 5.75

1. _____

2. 5.75

2. _____

3. 6.5

3. _____

Gun Length: _____

Primer Marking: _____

Gun Weight: _____

Safety Check: _____

Center of Gravity: _____

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

CJS
I-12-82

• Tester and Date: _____

After 2,500 Rounds

6-11-82

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 6MM

Serial No. A6752973

Headspace as Received: _____

Safe - "ON" - I. 6.5

"OFF" - I. 5.0

Proof: _____

(62) 2. 6.0
3. 6.0

(51) 2. 5.5
3. 5.0

Headspace after Proof: M + .004

Firing Pin Indent (in.)

I. .022

2. .022

3. .022

(22) *Severe
lift .011
eng. .016*

Bolt Open Force (lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull (lbs.)

I. 6.50

2. 6.25

3. 6.25

(63)

Bolt Release Force (lbs.)

I. _____

2. _____

3. _____

Gun Length: _____

Gun Weight: _____

Center of Gravity: _____

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: _____

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: _____

CJS

I-12-82