

Gun ①

TEST PROCEDURE SHEET

Model 700 300H+H Mag.

Serial No. B6415975

Headspace as Received: \_\_\_\_\_

Safe - "ON" - 1. 7.5

"OFF" - 1. 7.0

Proof: OK

2. 7.5

2. 7.5

Headspace after Proof: OK

3. 7.5

3. 7.0

Firing Pin Indent (in.)

1. 0.24

2. 0.245

3. 0.235

Bolt Open Force (lbs.)

Cocked: 1. \_\_\_\_\_

Dry Fired: 1. \_\_\_\_\_

2. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

3. \_\_\_\_\_

Trigger Pull (lbs.)

1. 3.75

2. 4.0

3. 4.0

Bolt Release Force (lbs.)

1. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

Gun Length: 44 1/4" center of batt

Primer Marking: \_\_\_\_\_

Gun Weight: 7 1/6 602.

Safety Check: \_\_\_\_\_

Center of Gravity: 1.4" Rear

Firing Pin Protrusion: \_\_\_\_\_

Bore: \_\_\_\_\_

Pattern Test (Avg. of 5)

Choke: \_\_\_\_\_

Group Size: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Vert.: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Accuracy (Avg. of 5)

Disconnecter Check: \_\_\_\_\_

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.C.I.: \_\_\_\_\_

CJS  
I-12-82

• Tester and Date: J. Baocetta

R. Williams

11-8-'82

Gun (2)

TEST PROCEDURE SHEET

Model 700 300H+H Mag

Serial No. 86416963

Headspace as Received: \_\_\_\_\_

Proof: OK

Headspace after Proof: OK

Firing Pin Indent (in.)

1. .0255

2. .025

3. .025

Trigger Pull (lbs.)

1. 4.25

2. 4.5

3. 4.5

Gun Length: 44 1/4" Center of butt

Gun Weight: 7 1/6 11oz.

Center of Gravity: 1.8" Rear

Bore: \_\_\_\_\_

Choke: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Disconnecter Check: \_\_\_\_\_

Safe - "ON" - 1. 6.5

2. 7.0

3. 7.0

"OFF" - 1. 6.5

2. 6.0

3. 6.5

Bolt Open Force (lbs.)

Cocked: 1. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

Dry Fired: 1. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

Bolt Release Force (lbs.)

1. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

Primer Marking: \_\_\_\_\_

Safety Check: \_\_\_\_\_

Firing Pin Protrusion: \_\_\_\_\_

Pattern Test (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_

Accuracy (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.O.I.: \_\_\_\_\_

• Tester and Date: J. Baggetta

R. Williams

11-8-82

CJS  
I-12-82

SHOWINGS, OPERATIONS, REPAIRS (PUMPS & AUTOCLEANERS)

Gun (3)

TEST PROCEDURE SHEET

Model 700 300H+H Mag.

Serial No. 86415094

Headspace as Received: \_\_\_\_\_

Safe - "ON" - I. 7.0

"OFF" - I. 5.5

Proof: OK

2. 7.5

2. 5.5

Headspace after Proof: OK

3. 7.5

3. 5.5

Firing Pin Indent (in.)

I. .025

2. .025

3. .024

Bolt Open Force (lbs.)

Cocked: I. \_\_\_\_\_

Dry Fired: I. \_\_\_\_\_

2. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

3. \_\_\_\_\_

Trigger Pull (lbs.)

I. 4.5

2. 4.25

3. 4.25

Bolt Release Force (lbs.)

I. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

Gun Length: 44 1/4" center of butt

Gun Weight: 7 lb. 6 oz.

Center of Gravity: 1.5" Rear

Bore: \_\_\_\_\_

Choke: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Disconnecter Check: \_\_\_\_\_

Primer Marking: \_\_\_\_\_

Safety Check: \_\_\_\_\_

Firing Pin Protrusion: \_\_\_\_\_

Pattern Test (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_

Accuracy (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ F.O.I.: \_\_\_\_\_

CJS  
I-12-82

• Tester and Date: J. Baggett

R. Williams

11-8-82

SHOTGUNS, REMINGTONS, REMINGTONS (PUMPS & AUTOMATICS)

Gun (4)

TEST PROCEDURE SHEET

Model 700 300H+H Mag.

Serial No. B6415093

Headspace as Received: \_\_\_\_\_

Safe - "ON" - 1. 7.5

"OFF" - 1. 5.5

Proof: OK

2. 7.0

2. 5.5

Headspace after Proof: OK

3. 7.0

3. 6.0

Firing Pin Indent (in.)

1. .0245

2. .025

3. .0245

Bolt Cuen Force (lbs.)

Cocked: 1. \_\_\_\_\_

Dry Fired: 1. \_\_\_\_\_

2. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

3. \_\_\_\_\_

Trigger Pull (lbs.)

1. 3.75

2. 4.0

3. 4.0

Bolt Release Force (lbs.)

1. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

Gun Length: 44 1/4" CENTER of Butt

Gun Weight: 716. 862.

Center of Gravity: 1.4" Rear

Bore: \_\_\_\_\_

Choke: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Disconnecter Check: \_\_\_\_\_

Primer Marking: \_\_\_\_\_

Safety Check: \_\_\_\_\_

Firing Pin Protrusion: \_\_\_\_\_

Pattern Test (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_

Accuracy (Avg. of 5)

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.O.I.: \_\_\_\_\_

CJS  
1-12-82

• Tester and Date: J. Baggett  
R. Williams  
11-8-82

SHOTGUNS, CENTERFIRES, RIFLES (PUMPS & AUTOLOADERS)

Gun (5)

TEST PROCEDURE SHEET

Model 700 300H+H Mag.

Serial No. B6415850

Headspace as Received: \_\_\_\_\_

Safe - "ON" - 1. 7.0 "OFF" - 1. 7.0

Proof: OK

2. 6.5 2. 7.0

Headspace after Proof: OK

3. 6.75 3. 7.25

Firing Pin Indent (in.)

Bolt Open Force (lbs.)

1. .0215

Cocked: 1. \_\_\_\_\_ Dry Fired: 1. \_\_\_\_\_

2. .0215

2. \_\_\_\_\_ 2. \_\_\_\_\_

3. .021

3. \_\_\_\_\_ 3. \_\_\_\_\_

Trigger Pull (lbs.)

Bolt Release Force (lbs.)

1. 4.25

1. \_\_\_\_\_

2. 3.75

2. \_\_\_\_\_

3. 4.0

3. \_\_\_\_\_

Gun Length: 44 1/4" center of butt

Primer Marking: \_\_\_\_\_

Gun Weight: 716.702

Safety Check: \_\_\_\_\_

Center of Gravity: 1.4" Rear

Firing Pin Protrusion: \_\_\_\_\_

Bore: \_\_\_\_\_

Pattern Test (Avg. of 5)

Choke: \_\_\_\_\_

Group Size: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Vert.: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Accuracy (Avg. of 5)

Disconnecter Check: \_\_\_\_\_

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.O.I.: \_\_\_\_\_

CJS  
I-12-82

• Tester and Date: S Baggetta  
R. Williams  
11-8-82

Gun ⑥

SHOTGUNS, CARTRIDGES, RIFLES (PUMP & AUTOCARTRIDGES)

TEST PROCEDURE SHEET

Model 700 300H+H Mag.

Serial No. B6415129

Headspace as Received: \_\_\_\_\_

Safe - "ON" - 1. 7.0 "OFF" - 1. 6.75

Proof: OK

2. 7.0 2. 6.5

Headspace after Proof: OK

3. 7.25 3. 6.75

Firing Pin Indent (in.)

Bolt Open Force (lbs.)

1. 0.25

Cocked: 1. \_\_\_\_\_ Dry Fired: 1. \_\_\_\_\_

2. 0.25

2. \_\_\_\_\_ 2. \_\_\_\_\_

3. 0.25

3. \_\_\_\_\_ 3. \_\_\_\_\_

Trigger Pull (lbs.)

Bolt Release Force (lbs.)

1. 4.0

1. \_\_\_\_\_

2. 4.25

2. \_\_\_\_\_

3. 4.25

3. \_\_\_\_\_

Gun Length: 44 1/4" center of butt

Primer Marking: \_\_\_\_\_

Gun Weight: 7 1/6 7.02

Safety Check: \_\_\_\_\_

Center of Gravity: 1.4" Rear

Firing Pin Protrusion: \_\_\_\_\_

Bore: \_\_\_\_\_

Pattern Test (Avg. of 5)

Choke: \_\_\_\_\_

Group Size: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Vert.: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Accuracy (Avg. of 5)

Disconnecter Check: \_\_\_\_\_

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.O.I.: \_\_\_\_\_

CJS  
I-12-82

• Tester and Date: J. Baggett  
R. Williams  
11-8-82

SECTION 1. GENERAL INFORMATION (PUMP & AUTOMATIC)

Gun (7)

TEST PROCEDURE SHEET

Model 700 300 H+H Mag.

Serial No. B6415107

Headspace as Received: \_\_\_\_\_

Safe - "ON" - 1. 7.25 "OFF" - 1. 5.75

Proof: OK

2. 7.25 2. 5.5

Headspace after Proof: OK

3. 7.0 3. 5.5

Firing Pin Indent (in.)

Bolt Coen Force (lbs.)

1. .025

Cocked: 1. \_\_\_\_\_ Dry Fired: 1. \_\_\_\_\_

2. .0245

2. \_\_\_\_\_

3. .025

3. \_\_\_\_\_

Trigger Pull (lbs.)

Bolt Release Force (lbs.)

1. 4.0

1. \_\_\_\_\_

2. 3.75

2. \_\_\_\_\_

3. 4.0

3. \_\_\_\_\_

Gun Length: 44 1/2" center of butt

Primer Marking: \_\_\_\_\_

Gun Weight: 716. 702.

Safety Check: \_\_\_\_\_

Center of Gravity: 1.3" Rear

Firing Pin Protrusion: \_\_\_\_\_

Bore: \_\_\_\_\_

Pattern Test (Avg. of 5)

Choke: \_\_\_\_\_

Group Size: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Vert.: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Accuracy (Avg. of 5)

Disconnecter Check: \_\_\_\_\_

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.O.I.: \_\_\_\_\_

CJS  
I-22-82

• Tester and Date: J. Baggetta

R. Williams

11-8-82

Gun ⑧

TEST PROCEDURE SHEET

Model 700 300H+H Mag.

Serial No. R6415143

Headspace as Received: \_\_\_\_\_

Safe - "ON" - 1. 6.75 "OFF" - 1. 5.25

Proof: OK

2. 6.5 2. 5.25

Headspace after Proof: OK

3. 6.5 3. 5.0

Firing Pin Indent (in.)

Bolt Open Force (lbs.)

1. .0245

Cocked: 1. \_\_\_\_\_ Dry Fired: 1. \_\_\_\_\_

2. .0245

2. \_\_\_\_\_ 2. \_\_\_\_\_

3. .025

3. \_\_\_\_\_ 3. \_\_\_\_\_

Trigger Pull (lbs.)

Bolt Release Force (lbs.)

1. 4.25

1. \_\_\_\_\_

2. 4.0

2. \_\_\_\_\_

3. 4.0

3. \_\_\_\_\_

Gun Length: 44 1/4" center of butt

Primer Marking: \_\_\_\_\_

Gun Weight: 7 lb. 4 oz.

Safety Check: \_\_\_\_\_

Center of Gravity: 1.2" Rear

Firing Pin Protrusion: \_\_\_\_\_

Bore: \_\_\_\_\_

Pattern Test (Avg. of 5)

Choke: \_\_\_\_\_

Group Size: \_\_\_\_\_

Orifice Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Bolt Closing Velocity: \_\_\_\_\_

Vert.: \_\_\_\_\_

Magazine Spring Force: \_\_\_\_\_

Accuracy (Avg. of 5)

Disconnecter Check: \_\_\_\_\_

Group Size: \_\_\_\_\_

Horz.: \_\_\_\_\_

Vert.: \_\_\_\_\_ P.O.I.: \_\_\_\_\_

CJS  
I-12-82

• Tester and Date: J. Baagetta  
R. Williams

11-8-82

300 H+H MAG 20Gr. PSP. Remi: 3Ton

1. B6415975 3.20  
2.20  
2.95

Avg. 2.79

4. B6415093 2.5  
2.5  
2.2

Avg 2.40

6 B6415129 2.80  
2.45  
2.85

Avg 2.70

7 B6415107 2.20  
1.50  
1.90

Avg 1.87