

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 ADL R-type Gun (1)

Serial No. B6408648

Headspace as Received: _____

Safe - "ON" - 1. 7.50

"OFF" - 1. 8.00

2. 7.50

2. 7.50

3. 7.50

3. 7.50

Proof: _____

Headspace after Proof: MINT. 003

Bolt Open Force (lbs.)

Cocked: 1. _____

Dry Fired: 1. _____

2. _____

2. _____

3. _____

3. _____

Firing Pin Indent (in.)

1. .0245

2. .025

3. .0245

Trigger Pull (lbs.)

1. 4.75

2. 4.75

3. 4.50

Bolt Release Force (lbs.)

1. _____

2. _____

3. _____

Gun Length: 42.5"

Gun Weight: 6 lbs 14 oz.

Center of Gravity: 1.4" Rear

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnect Check: _____

Lock Time 3.40 MS

Primer Marking: _____

Safety Check: _____

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: J B & P.W.

9-23-82

CJS
1-12-82

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700ADL Restyle Gun (2)

Serial No. 56407981

Headspace as Received: _____

Safe - "ON" - 1. 8.5 "OFF" - 1. 8.5

2. 8.0 2. 9.0

3. 8.5 3. 9.5

Proof: _____

Headspace after Proof: Min 1.003

Firing Pin Indent (in.)

1. .0225

2. .0235

3. .0225

Bolt Open Force (lbs.)

Cocked: 1. _____ Dry Fired: 1. _____

2. _____ 2. _____

3. _____ 3. _____

Trigger Pull (lbs.)

1. 4.0

2. 4.0

3. 4.0

Bolt Release Force (lbs.)

1. _____

2. _____

3. _____

Gun Length: 42.5"

Gun Weight: 6 1/2, 13oz.

Center of Gravity: 1.2" Rear

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Lock Time 3.45 ms

Primer Marking: _____

Safety Check: _____

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

• Tester and Date: J.B. & R.W.

9-23-82

CJS
I-12-82

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700ADL Restyle ^{Q₄₁} (9)

Serial No. B6407773

Headspace as Received: _____

Safe - "ON" - I. 9.5 "OFF" - I. 6.5

Proof: _____

2. 9.5 2. 6.0

Headspace after Proof: MIN 7.003

3. 9.0 3. 6.0

Firing Pin Indent(in.)

Bolt Open Force(lbs.)

I. .022

Cocked: I. _____ Dry Fired: I. _____

2. .022

2. _____ 2. _____

3. .0235

3. _____ 3. _____

Trigger Pull(lbs.)

Bolt Release Force(lbs.)

I. 4.5

I. _____

2. 4.5

2. _____

3. 4.5

3. _____

Gun Length: 42.5"

Primer Marking: _____

Gun Weight: 7lbs. 2oz.

Safety Check: _____

Center of Gravity: 1.6" Rear

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

CJS
I-12-82

• Tester and Date: J.B. & R.W.

9-23-82

SHOTGUNS, CENTERFIRES, RIFLES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700ADL Restyle

Gun (4)

Serial No. B6407475

Headstace as Received: _____

Safe - "ON" - I. 9.5

"OFF" - I. 6.5

Proof: _____

2. 9.0

2. 6.5

Headspace after Proof: Min 7.003

3. 9.0

3. 6.5

Firing Pin Indent(in.)

Bolt Open Force(lbs.)

I. .024

Cocked: I. _____

Dry Fired: I. _____

2. .0225

2. _____

2. _____

3. .0235

3. _____

3. _____

Trigger Pull(lbs.)

Bolt Release Force(lbs.)

I. 4.25

I. _____

2. 4.50

2. _____

3. 4.5

3. _____

Gun Length: 42.5"

Primer Marking: _____

Gun Weight: 6lbs. 10oz

Safety Check: _____

Center of Gravity: 1" Rear

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

CJS
I-12-82

• Tester and Date: J.B. & K.W.

9-23-82

SHOTGUNS, CENTERFIRES, RIFLES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 ADL Restyle

Serial No. B6408155

Gun (5)

Headspace as Received: _____

Safe - "ON" - I. 7.5

"OFF" - I. 9.0

2. 7.5

2. 8.5

3. 8.0

3. 9.5

Proof: _____

Headspace after Proof: Min +.003

Firing Pin Indent(in.)

I. .020

2. .0205

3. .0215

Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

I. 4.0

2. 3.5

3. 4.0

Bolt Release Force(lbs.)

I. _____

2. _____

3. _____

Gun Length: 42.5"

Gun Weight: 7lbs. 2.02

Center of Gravity: 1.7"

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: _____

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

CJS
I-12-82

• Tester and Date: J.B. C.P.W.
9-23-82

SHOTGUNS, CENTERFIRES, RIMFIRES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700 ADL Restyle

Serial No. B6407794

Gun (7)

Headspace as Received: _____

Safe - "ON" - I. 8.5

"OFF" - I. 7.5

2. 8.0

2. 7.0

3. 7.5

3. 7.0

Proof: _____

Headspace after Proof: Min +.003

Firing Pin Indent(in.)

1. .0215

2. .0215

3. .021

Bolt Open Force(lbs.)

Cocked: I. _____

Dry Fired: I. _____

2. _____

2. _____

3. _____

3. _____

Trigger Pull(lbs.)

1. 4.75

2. 4.5

3. 4.5

Bolt Release Force(lbs.)

I. _____

2. _____

3. _____

Gun Length: 42.5"

Gun Weight: 6 lbs. 10 oz.

Center of Gravity: 1.1 Rear

Bore: _____

Choke: _____

Orifice Size: _____

Bolt Closing Velocity: _____

Magazine Spring Force: _____

Disconnecter Check: _____

Primer Marking: _____

Safety Check: _____

Firing Pin Protrusion: _____

Pattern Test (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____

Accuracy (Avg. of 5)

Group Size: _____

Horz.: _____

Vert.: _____ P.O.I.: _____

CJS
I-12-82

• Tester and Date: J.B. & R.W.

9-23-82

SHOTGUNS, CENTERFIRES, RIFLES (PUMPS & AUTOLOADERS)

TEST PROCEDURE SHEET

Model 700ADL Restyle

Gun 8

Serial No. B6407263

Headspace as Received: _____

Safe - "ON" - 1. 8.0

"OFF" - 1. 5.5

Proof: _____

2. 8.0

2. 4.5

Headspace after Proof: Min + .003

3. 7.5

3. 4.75

Firing Pin Indent(in.)

Bolt Open Force(lbs.)

1. .023

Cocked: 1. _____

Dry Fired: 1. _____

2. .0225

2. _____

2. _____

3. .024

3. _____

3. _____

Trigger Pull(lbs.)

Bolt Release Force(lbs.)

1. 4.0

1. _____

2. 4.0

2. _____

3. 4.0

3. _____

Gun Length: 42.5"

Primer Marking: _____

Gun Weight: 6 lbs. 15 oz.

Safety Check: _____

Center of Gravity: 1.3 Rear

Firing Pin Protrusion: _____

Bore: _____

Pattern Test (Avg. of 5)

Choke: _____

Group Size: _____

Orifice Size: _____

Horz.: _____

Bolt Closing Velocity: _____

Vert.: _____

Magazine Spring Force: _____

Accuracy (Avg. of 5)

Disconnecter Check: _____

Group Size: _____

Lock Time 3.30 MS

Horz.: _____

Vert.: _____ P.O.I.: _____

CJS
I-12-82

• Tester and Date: J.B. & P.W.
9-23-82