

RECEIVER MEASUREMENTS

MODEL 700

(9 AOL, 23 BOL RIFLES)

DWG. NO.	SERIAL NO.	MIN.	MAX.	MEAN	ACTUAL DIMENSIONS
MEASUREMENT NO.					
1	1	1.700	1.730	1.715	1.870
2	2	.015	.018	.0165	.014
3	3	13° REF L			13°
4	4	.245	.255	.250	.235
5	5	2.045	2.055	2.050	2.067
6	6				
7	7	.695	.705	.700	.785
8	8	.020 R			.010 R
9	9	33			63
10	10	.055	.065	.060	.058
11	11	30°			30°
12	12	.281 TYP			.281 TYP
13	13	.163	.173	.168	.1695
13a	13a	.163	.173	.168	.1695
14	14	4.4075	4.4175	4.4125	4.534
15	15	7/16 R TYP			NONE
16	16	.535	.545	.540	.533
17	17	.968	.978	.973	.972
18	18	.180 R	.205 R	.1925 R	.200 R
19	19	.072 GAGE			.072
20	20	2.936	2.944	2.940	2.943
21	21	.180 R	.205 R	.1925 R	.200 R
22	22	.835	.845	.840	.848
23	23	4.530	4.535	4.5325	4.534
24	24	37°			36°
25	25	.282	.288	.285	.289
25a	25a	.282	.288	.285	.289
26	26	.055	.063	.059	.060
27	27	.278 R	.280 R	.279 R	.280 R
28	28	.700	.703	.7015	.702
29	29	.449	.452	.4505	.450
30	30	.015	.025	.020	.030
31	31	20°			20°
32	32	.025 R			.010 R
33	33	ROUND OFF SHARP CORNERS			SHARP
34	34	STRAIGHT & PARALLEL			11
35	35				
36	36	.004	.004	±.004	±.004