

RECEIVER MEASUREMENTS

MODEL 700

(2 ADL, 23 BOL RIFLES)

(11)

DWG. NO.	SERIAL NO.	DWG. DIMENSIONS			ACTUAL DIMENSIONS	
		MIN.	MAX.	MEAN		
	MEASUREMENT NO.					
D-33580	1	1.700	1.730	1.715	1.755	10
	2	.015	.018	.0165	.015	✓
	3	13°	REF L.		13°	✓
	4	.245	.255	.250	.300	9
	5	2.045	2.055	2.050	2.065	8
	6					7
	7	.695	.705	.700	.780	6
	8	.020 R			.005 R	5
	9	32			32	4
	10	.055	.065	.060	.065	✓
	11	30°			30°	✓
	12	.281	TYR		.281	TYR
	13	.163	.173	.168	.170	
	13a	.163	.173	.168	.170	✓
	14	4.4075	4.4175	4.4125	4.533	3
E-33215	15	7/16 R	TYR		NONE	2
	16	.535	.545	.540	.537	✓
	17	.968	.978	.973	.967	
	18	.180 R	.205 R	.1925 R	.190 R	✓
	19	.072	BAGE		.072	✓
	20	2.936	2.944	2.940	2.945	
	21	.180 R	.205 R	.1925 R	.190 R	
	22	.835	.845	.840	.840	✓
	23	4.530	4.535	4.5325	4.533	✓
	24	37°			37°	✓
	25	.282	.288	.285	.287	
	25a	.282	.288	.285	.287	✓
	26	.055	.063	.059	.055	✓
	27	.278 R	.280 R	.279 R	.280 R	✓
	28	.700	.703	.7015	.702	✓
	29	.449	.452	.4505	.450	✓
	30	.015	.025	.020	.025	✓
	31	20°			20°	✓
	32	.025 R			.005 R	1
	33	ROUND OFF SHARP CORNERS			SHARP	11
	34	STRAIGHT & PARALLEL			11	✓
	35					
	36	.004	.004	±.004	±.000 -.001	