# REMINGTON ARMS COMPANY, INC.

INTER-DEPARTMENTAL CORRESPONDENCE

Remineton

"CONFINE YOUR LETTER TO ONE SUBJECT ONLY"\_\_\_\_\_

RESEARCH TEST and MEASUREMENT REPORT - Report No. 832091

PRODUCTION MODEL XP-100 - 7MM BR - 1000 ROUND ENDURANCE TEST

Prepared by: R. W. Howe

Date Prepared: August 18, 1983

Distribution: C. B. Workman

Preciread and Caared By:

J.H. Hennings , R.Z. Nightingale,
Foreman-Measurement Lab

Signature Day htigall

C.E. Rimbie.

Sr. Supervisor - Testing, Mess. & Mech. Analysis Lab KABILLY 1/31 AVILLY 11

#### TEST & MEASUREMENT LAB REPORT

REPORT NUMBER:	832091
REPORT TITLE:	Production Model XP-100 - 7MM BR - 1000 Round Endurance Test
MODEL(S):	XP-100
GAUGE OR CALIBER:	7MM BR
DATE:	8-18-83
WORK ORDER NO.:	G-0459-000 X
PART NAME:	XP-100 Pistol
DESIGNER/ENGINEER:	
TEST TYPE:	
1.	PHOTO LAB
2.	STRENGTH TEST - NO. OF GUNS TESTED
3.	FUNCTION TEST - NO. OF GUNS TESTED
4.	ACCURACY TEST - NO. OF GUNS TESTED
5.	MEASUREMENTS - TYPE:
6.	ENVIRONMENTAL TEST
7.	Ammunition testing & evaluation - type:
8.	VISUAL EVALUATIONOUT OFGUN SAMPLE
9.	ENDURANCE - NO. OF GUNS TESTED: 1
	NO. OF ROUNDS FER GUN: 1000
	TOTAL ROUNDS FIRED IN TEST: 1000
	AMMO TYPE: MAGS; TARGET:
	RIM FIRECENTER FIRE X

August 18, 1983

TO:

C. E. RITCHIE

FROM:

R. W. HOWE

REPORT TITLE:

PRODUCTION MODEL XP-100 - 7MM BR - 1000 ROUND

**ENDURANCE TEST** 

#### **ABSTRACT**

On 7-28-83, one Production Model XP-100 - 7MM BR caliber, was received in the R. & D. Test Lab from C. E. Ritchie, Firearms Research Supervisor, to be 1,000 live round endurance tested in the R. & D. Test Lab Shooting Room jacks.

#### SCOPE OF TEST

To evaluate the function of the Model XP-100 pistol in the 7MM BR Caliber.

#### TEST RESULTS

Of the 1000 live rounds jack fired in the test pistol, Serial No. B7519039, no malfunctions or non-acceptable safety conditions were encountered.

## REPORT TEXT

A. Head Space, Chamber Pressure and Muzzle Velocity measurements were taken, and found to be within Remington acceptable standards at the start of the test.

Present Remington Standards - Head Space - Min. to Min. + .009 Chamber Pressure - 5500 lbs. PSI Muzzle Velocity - 2100 FPS

#### B. Jack Function Test:

Acceptable standards are determined by percentage of malfunctions with severity of malfunctions being considered.

Of the 1000 live rounds jack fired in the test pistol, no malfunctions were encountered, for a malfunction rate of 0% for the total 1000 round test.

Refer to Appendix "A" Sheets 1 to 3 for data.

#### TEST PROCEDURE

#### A. Measurements:

Measurements were taken in the R. & D. Test Lab using the following methods:

- 1. Head Space
  - Head Space measurements were taken using 7MM BR head space gauges ranging from Min. + Min. + .009.
- 2. Chamber Pressure
  Chamber pressures were taken in the R. & D. Measurements Lab using a Universal Receiver fitted with a pressure barrel and PCB. Pielo Electric Pressure Transducer.
- 3. Muzzle Velocity
  - Muzzle velocity measurements were taken in the R. & D. Measurements Lab using the Lab's balistics screens.
- B.

The Jack Function Test was done in the R. & D Test Lab Shooting Room in Booth No. 5 using the XP-100 pistol fixture attached to the regular permanent rifle and shotgun shooting jack. 1,000 rounds of the following 7MM BR hand loads were shot (cooling the pistol with compressed air every 100 rounds):

25 Gr. of DuPont No. 4198 Powder Rem. 71/2 BR Primer 150 Gr. Rem. 7MM P.S.P. Bullet

For Data, See Appendix "A" Sheets 1 to 3.

APPENDIX "A"

(Data Sheets)

Results of Remington Model XP-100 — 7MM BR (Serial No. B7519039) 1000 Round Endurance Test pursuant to subdivision 12A, Section Four Hundred, Sub-title K of Title Nine Part 482.6 Safety Standards Test, Item No. 2, Appendix B, Table No. 1 Pistol Endurance, of the Penal Law of the State of New York.

Malfunctions and Non-Acceptable Conditions	Failures Permitted 1000 Rounds	Failures Encountered in XP-100 Test Gun
1. Failure of Sear to Release	0	· <b>0</b>
2. Gas Leakage Through Case	0 -	0
3. Safety Device Fails to Function	0	0
4. More than one shot fired for a single pull of the trigger.	0	0

# Measurement Results of XP-100 - 7MM BR Cal. Test Gun Serial No. B7519039.

 Head Space Min. Present Rem. Standard Min. to Min. + .009"

2. Chamber Pressure 55,000 lbs. P.S.I.

55,000 lbs. P.S.I.

3. Muzzle Velocity 2180 F.P.S.

2100 F.P.S.

### Ammo used in test:

7MM BR Hand Loads. 25 Gr. of DuPont No. 4198 Powder. Remington 7½ BR Primer 150 Gr. Remington Pointed Soft Point Bullet.

TITLE WOLL TEST	- CENTERF
TACK ENDURA	NCE TEST

APPENDIX A"
SHEET #3

NEPROT NO.1832091

F	No.
-	no,

M18:8-17-83

HODELI XP100

GATHET THABE

BERIAL NO. <u>B7579039</u>

EUROI VERTI ECHNUON

TEST TITLE, ENGURANCE TO 1000, P.L.

TTL. RDS. FIRED: 1000
TTL. MALFUNCTIONS: 0
MALFUNCTION RATE:

										H	WIF	unct	10N8	11							1	Malf	unci	ION	nate	·	 
HAND LONDS 2591. 4198 11/2 BE PRIME! 15091 REM 130/1ET		REMINIS FIRED		SEECL		ALCS BACK	LOCK OPEN	FR	ed om	STEMS MAG.	OVERRIDE	TOCK UP		g1 CHA	em Mben		JUMPS MAG.	POLLOWER BINIS		स्तर का	<b>到</b>	I JACI	82		Sprais	ì	
	SECOCES	10° 05	73578	TOWN COMMEN	DON'T RADE	四 1. 图2	T. T. E	1	icil Sug		POWER (		<u> </u>	LOW	arena i		THES	POLLOW	LOADING	BOLT OVERRIDE	ACCION BANG UP	DOM'T ENTRACT	महत्त्र हात्वर	A DATES THE SERVERS	REPLACEMENTS		
HernidLoad	BH	100	or																								
		100	<u></u>		_															-							
		100	<u></u>			_	_																				
	_	110	<u></u>		_	_		_				_															
		100	·,					_		_										_			_				 
		100	<u> </u>			_				_						_	_	_				_					
··········	<b> </b>	100	<u></u>			_		_		_		_						Ŀ									 
,		10	<u></u>					_			<b> </b>	_		_	_		_										
•		100	<u> </u>	_		_	_			<b> </b>						i 											
·		101	<u>:-</u>		<b> </b>		_													_		<u>'</u>	_				
-	/			<u> </u>							_	_	_				_									~	
				_																							
TOTAL (PER MAL.)		1000			<u></u>	<u> </u>																					