

REMINGTON ARMS COMPANY, INC.

INTER-DEPARTMENTAL CORRESPONDENCE



"CONFINE YOUR LETTER TO ONE SUBJECT ONLY" _____

June 19, 1985

TO: J.W. Bower
W.L. Tomek
R.S. Murphy
F.E. Martin
File

FROM: F.H. Smith

NBAR EXTRACTOR TESTING

Objective: To dry-cycle the NBAR extractor designs and the M/700 extractor 50,000 cycles and compare performance characteristics.

Goal: To improve upon the M/700's extractor performance, if possible.

Extractors

Tested: M/700 rivetless design; NBAR 1st design, NBAR 2nd design

Method: R. Howe, Test and Measurement Lab, built a testing device that would deflect the extractor approximately .040", simulating the movement required when the bolt is closed over a round in the gun. The device then retracts and the springing action of the extractor returns the activating arm, simulating ejection of a round.

Results: NBAR 1st and 2nd designs went 50,000 cycles with no malfunctions or breakages.

M/700 Design

- o At 8,000 cycles extractor stuck back and had to be freed.
- o At 9,500 and 9,700 cycles approximately, extractor stuck again and had to be freed.

NBAR Extractor Testing

Page 2

June 19, 1985

M/700 Design - cont'd.

- o Extractor stuck again approximately every 50 rounds up to 10,048 rounds when the extractor was taken out of test.
- o Extractor required a 4 lb. force to deflect it at the beginning of the test and 3-1/2 lbs. after testing was stopped.

HS:sps