

SAAMI SPEC.
"JAR OFF TEST"

5/8/90 After
Trig. Adj

FIREARM # B7532032

REPORT #

MODEL X P100 R

W.O. #

TRIGGER Pull LBS _____ TEST TITLE _____

SAAMI SPEC JAR OFF TEST = 12" DROP MEASURED FROM
LOWEST PART OF GUN. ONE DROP IN EACH OF FOLLOWING
POSITIONS AGAINST A 1", 85 $\pm$ 5 DUROMETER "SHORE A"
RUBBER MATT BACKED BY CONCRETE W/ SAFETY LEVER IN
"OFF" POSITION.

	12" DROP SAFE OFF	(V = OK J.O. = JAR OFF)
BAR. VERT MUZZLE UP	<u>✓</u>	
" " " DOWN	<u>✓</u>	
BAR. HORIZ. BOTTOM UP	<u>JO</u>	
" " " DOWN	<u>✓</u>	
" " LEFT SIDE UP	<u>✓</u>	
" " RIGHT SIDE UP	<u>✓</u>	

"DROP TEST"
48" SAFE "ON" POSITION.

(DROP 48" FROM CENTER
OF GRAVITY OF FIRE ARM.)

BAR. VERT MUZZLE UP	<u>✓</u>
" " " DOWN	<u>✓</u>
BAR. HORIZ. BOTTOM UP	<u>✓</u>
" " " DOWN	<u>✓</u>
" " LEFT SIDE UP	<u>✓</u>
" " RIGHT SIDE UP	<u>✓</u>

"ROTATION TEST"

BUT ON MAT LET FIRE ARM FALL TO LEFT + RIGHT

LEFT SIDE UP . N.A.

RIGHT SIDE UP N.A.

XP100R

7/11/08 .

2035.

+ .002

+ .003

2032

+ .001

+ .001

1974

+ .003

+ .004

gg3

1730

+ .001

+ .002

1715

+ .001

+ .001

#1

B7531730

#2

B7531715

#3

B7531998

#4


B7532062

B7532078

B7532032

B7531974

B7532035







SAAMI SPEC.
"JAR OFF TEST"

FIREARM # 87532032

REPORT # _____

MODEL XPI00R 7-08

W.O. # _____

TRIGGER Pull LBS 2.9lb TEST TITLE _____

SAAMI SPEC JAR OFF TEST = 12" DROP MEASURED FROM LOWEST PART OF GUN. ONE DROP IN EACH OF FOLLOWING POSITIONS AGAINST A 1", 85 +/- 5 DUROMETER "SHORE A" RUBBER MAT BACKED BY CONCRETE W/ SAFETY LOVER IN "OFF" POSITION.

	12" DROP SAFE OFF	(V = OK J.O. = JAR OFF)
BAR. VERT MUZZLE UP	<u>J.O.</u>	
" " " DOWN	<u>✓</u>	
BAR HORIZ. BOTTOM UP	<u>✓</u>	
" " " DOWN	<u>✓</u>	
" " LEFT SIDE UP	<u>✓</u>	
" " RIGHT SIDE UP	<u>✓</u>	

"DROP TEST"
48" SAFE "ON" POSITION.

(DROP 48" FROM CENTER OF GRAVITY OF FIRE ARM.)

BAR. VERT MUZZLE UP	<u>✓</u>
" " " DOWN	<u>✓</u>
BAR. HORIZ. BOTTOM UP	<u>✓</u>
" " " DOWN	<u>✓</u>
" " LEFT SIDE UP	<u>✓</u>
" " RIGHT SIDE UP	<u>✓</u>

"ROTATION TEST"

BUTT ON MAT LET FIRE ARM FALL TO LEFT & RIGHT

LEFT SIDE UP	<u>NA</u>
RIGHT SIDE UP	<u>NA</u>

SAAMI SPEC.
"JAR OFF TEST"

FIREARM # B7521715

REPORT # _____

MODEL XP100R 22 Rem

W.O. # _____

TRIGGER PULL LBS 3.6 TEST TITLE _____

SAAMI SPEC JAR OFF TEST = 12" DROP MEASURED FROM LOWEST PART OF GUN. ONE DROP IN EACH OF FOLLOWING POSITIONS AGAINST A 1", 85 $\pm$ 5 DUROMETER "SHORE A" RUBBER MAT BACKED BY CONCRETE W/ SAFETY LEVER IN "OFF" POSITION.

	12" DROP SAFE OFF	(V = OK J.O. = JAR OFF)
BAR. VERT MUZZLE UP	<u>✓</u>	
" " " DOWN	<u>✓</u>	
BAR. HORIZ. BOTTOM UP	<u>✓</u>	
" " " DOWN	<u>✓</u>	
" " LEFT SIDE UP	<u>✓</u>	
" " RIGHT SIDE UP	<u>✓</u>	

"DROP TEST"
48" SAFE "ON" POSITION.

(DROP 48" FROM CENTER OF GRAVITY OF FIRE ARM.)

BAR. VERT MUZZLE UP	<u>✓</u>
" " " DOWN	<u>✓</u>
BAR. HORIZ. BOTTOM UP	<u>✓</u>
" " " DOWN	<u>✓</u>
" " LEFT SIDE UP	<u>✓</u>
" " RIGHT SIDE UP	<u>✓</u>

"ROTATION TEST"

BUTT ON MAT LET FIRE ARM FALL TO LEFT + RIGHT

LEFT SIDE UP NA
RIGHT SIDE UP NA

SAAMI SPEC.
"JAR OFF TEST"

FIREARM # B7532078

REPORT #

MODEL XPI00R 35REM

W.O. #

TRIGGER Pull LBS 3.2 TEST TITLE

SAAMI SPEC JAR OFF TEST = 12" DROP MEASURED FROM LOWEST PART OF GUN. ONE DROP IN EACH OF FOLLOWING POSITIONS AGAINST A 1", 85 $\pm$ 5 DUROMETER "SHORE A" RUBBER MAT BACKED BY CONCRETE W/ SAFETY LEVER IN "OFF" POSITION.

	12" DROP SAFE OFF	(V = OK J.O. = JAR OFF)
BAR. VERT MUZZLE UP	✓	
" " " DOWN	✓	
BAR HORIZ. BOTTOM UP	✓	
" " " DOWN	✓	
" " LEFT SIDE UP	✓	
" " RIGHT SIDE UP	✓	

"DROP TEST"
48" SAFE "ON" POSITION.

(DROP 48" FROM CENTER OF GRAVITY OF FIRE ARM.)

BAR. VERT MUZZLE UP	✓
" " " DOWN	✓
BAR. HORIZ. BOTTOM UP	✓
" " " DOWN	✓
" " LEFT SIDE UP	✓
" " RIGHT SIDE UP	✓

"ROTATION TEST"

BUT ON MAT LET FIRE ARM FALL TO LEFT + RIGHT

LEFT SIDE UP NA
RIGHT SIDE UP NA