

SAAMI DROP TEST

TEST TITLE _____

REPORT # _____

W.O.# _____

DATE 5-30-90

MODEL XP100R

SERIAL# B7531215

TRIGGER PULL (LBS.) 5.0

COMMENTS CURRENT GRID M/700 FIRE CONTROL

SAAMI SPEC: JAR OFF TEST IS 12 INCH DROP, WITH SAFE IN "OFF" POSITION, MEASURED FROM THE LOWEST POINT OF GUN.
ONE DROP IN EACH OF THE FOLLOWING POSITIONS AGAINST A 1 INCH, 85 +/- 5 DUROMETER "SHORE A" RUBBER MAT BACKED BY CONCRETE.

12 INCH DROP (SAFE OFF)

BARREL VERTICAL, MUZZLE UP

OK

18"

OK

24"

OK

BARREL VERTICAL, MUZZLE DOWN

OK

OK

OK

BARREL HORIZONTAL, BOTTOM DOWN

OK

OK

OK

BARREL HORIZONTAL, BOTTOM UP

OK

OK

OK

BARREL HORIZONTAL, LEFT SIDE UP

OK

OK

OK

BARREL HORIZONTAL, RIGHT SIDE UP

OK

OK

OK

48 INCH DROP (SAFE ON)

NOTE: DROP IS 48 INCHES FROM THE CENTER OF GRAVITY OF THE FIREARM

BARREL VERTICAL, MUZZLE UP

OK

BARREL VERTICAL, MUZZLE DOWN

OK

BARREL HORIZONTAL, BOTTOM DOWN

OK

BARREL HORIZONTAL, BOTTOM UP

OK

BARREL HORIZONTAL, LEFT SIDE UP

OK

BARREL HORIZONTAL, RIGHT SIDE UP

OK

"ROTATION TEST"

BUTT ON MAT, LET FIREARM FALL TO LEFT AND RIGHT

LEFT SIDE UP

OK

RIGHT SIDE UP

OK