

SAAMI DROP TEST

TEST TITLE _____
 REPORT # _____ W.O.# _____ DATE 5-30-90
 MODEL XP100R SERIAL# B7532078 TRIGGER PULL (LBS.) 4.5
 COMMENTS CURRENT PROD. M/700 FIRE CONTROL

SAAMI SPEC: JAR OFF TEST IS 12 INCH DROP, WITH SAFE IN "OFF" POSITION, MEASURED FROM THE LOWEST POINT OF GUN.
 ONE DROP IN EACH OF THE FOLLOWING POSITIONS AGAINST A 1 INCH, 85 +/- 5 DUROMETER "SHORE A" RUBBER MAT BACKED BY CONCRETE.

12 INCH DROP (SAFE OFF)

		18"	24"
BARREL VERTICAL, MUZZLE UP	<u>OK</u>	<u>OK</u>	<u>OK</u>
BARREL VERTICAL, MUZZLE DOWN	<u>OK</u>	<u>OK</u>	<u>OK</u>
BARREL HORIZONTAL, BOTTOM DOWN	<u>OK</u>	<u>OK</u>	<u>* JO</u>
BARREL HORIZONTAL, BOTTOM UP	<u>OK</u>	<u>OK</u>	<u>OK</u>
BARREL HORIZONTAL, LEFT SIDE UP	<u>OK</u>	<u>OK</u>	<u>OK</u>
BARREL HORIZONTAL, RIGHT SIDE UP	<u>OK</u>	<u>OK</u>	<u>OK</u>

48 INCH DROP (SAFE ON)

NOTE: DROP IS 48 INCHES FROM THE CENTER OF GRAVITY OF THE FIREARM

BARREL VERTICAL, MUZZLE UP	<u>OK</u>
BARREL VERTICAL, MUZZLE DOWN	<u>OK</u>
BARREL HORIZONTAL, BOTTOM DOWN	<u>OK</u>
BARREL HORIZONTAL, BOTTOM UP	<u>OK</u>
BARREL HORIZONTAL, LEFT SIDE UP	<u>OK</u>
BARREL HORIZONTAL, RIGHT SIDE UP	<u>OK</u> ← SAFE ARM BROKE OFF

"ROTATION TEST"

BUTT ON MAT, LET FIREARM FALL TO LEFT AND RIGHT

LEFT SIDE UP	<u>OK</u>
RIGHT SIDE UP	<u>OK</u>

* AFTER ID. AT 24" BB HORZ. GUN WAS DROPPED IN THIS POSITION EIGHT MORE TIMES WITH NO ID.