

MODEL 700 STAINLESS STEEL, DESIGN ACCEPTANCE

APPENDIX B

CAL	SERIAL#	ACCURACY			
		Group	0 rounds	2000 rds.	4000 rds.
2506	C6678189	1	1.58	1.21	2.54
		2	1.21	2.00	2.90
		3	1.61	1.66	1.83
		AVG.	1.47	1.62	2.42*
2506	C6678195	1	1.83	1.51	2.45
		2	2.39	1.99	2.65
		3	2.09	2.43	1.78
		AVG.	2.10	1.98	2.29*
3006	C6706171	1	1.96	1.05	1.67
		2	2.36	1.44	2.19
		3	1.66	1.97	1.20
		AVG.	1.99	1.49	1.68
3006	C6671716	1	1.80	1.06	1.86
		2	2.59	1.62	2.10
		3	2.02	1.51	2.06
		AVG.	2.14	1.40	2.00
270	C6678194	1	1.52	2.39	3.56
		2	1.81	2.26	3.17
		3	2.35	1.88	3.83
		AVG.	1.90	2.18	3.52**
270	C6706173	1	2.12	2.30	2.02
		2	2.84	2.01	2.16
		3	2.92	2.51	3.01
		AVG.	2.63	2.27	2.40
280	C6706177	1	1.17	.85	1.43
		2	2.34	1.23	1.27
		3	1.97	1.51	.49
		AVG.	1.82	1.20	1.06
280	C6706176	1	1.04	1.23	1.39
		2	1.99	1.73	1.81
		3	1.43	1.32	1.86
		AVG.	1.49	1.43	1.69

* Out of zero round specification of 2.2 inches.

** Out of zero round specification of 3.5 inches.