

SAAMI DROP TEST

TEST TITLE Stainless Steel D.A.  
 REPORT # 720431 W.O.# 481167 DATE 4/21/92  
 MODEL 700 SERIAL# C6678176 TRIGGER PULL (LBS.) 4.4lb  
 COMMENTS 270wz - 0 rounds

SAAMI SPEC: JAR OFF TEST IS 12 INCH DROP, WITH SAFE IN "OFF" POSITION, MEASURED FROM THE LOWEST POINT OF GUN.  
 ONE DROP IN EACH OF THE FOLLOWING POSITIONS AGAINST A 1 INCH, 85 +/- 5 DUROMETER "SHORE A" RUBBER MAT BACKED BY CONCRETE.

12 INCH DROP (SAFE OFF)

BARREL VERTICAL, MUZZLE UP	<u>OK</u>
BARREL VERTICAL, MUZZLE DOWN	<u>OK</u>
BARREL HORIZONTAL, BOTTOM DOWN	<u>OK</u>
BARREL HORIZONTAL, BOTTOM UP	<u>OK</u>
BARREL HORIZONTAL, LEFT SIDE UP	<u>OK</u>
BARREL HORIZONTAL, RIGHT SIDE UP	

48 INCH DROP (SAFE ON)

NOTE: DROP IS 48 INCHES FROM THE CENTER OF GRAVITY OF THE FIREARM

BARREL VERTICAL, MUZZLE UP	<u>OK</u>
BARREL VERTICAL, MUZZLE DOWN	<u>OK</u>
BARREL HORIZONTAL, BOTTOM DOWN	<u>OK</u>
BARREL HORIZONTAL, BOTTOM UP	<u>OK</u>
BARREL HORIZONTAL, LEFT SIDE UP	<u>OK</u>
BARREL HORIZONTAL, RIGHT SIDE UP	

"ROTATION TEST"

BUTT ON MAT, LET FIREARM FALL TO LEFT AND RIGHT

LEFT SIDE UP	<u>OK</u>
RIGHT SIDE UP	<u>OK</u>