SAAMI DROP TEST

TEST TITLE STAINLESS STEE D. A.	
REPORT # 920431 W.O.# 481167	DATE 4/21/92
MODEL 700 SERIAL# C6678174	TRIGGER PULL (LBS.) 4.3 16c.
COMMENTS 7 WLy Mag - 10,000 rds.	
SAAMI SPEC: JAR OFF TEST IS 12 INCH DROP, W FROM THE LOWEST POINT OF GUN. ONE DROP IN EACH OF THE FOLLOWI +/- 5 DUROMETER "SHORE A" RUBBE	ING POSITIONS AGAINST A 1 INCH, 85
12 INCH DROP (SAFE OFF)	
BARREL VERTICAL, MUZZLE UP	<u> </u>
BARREL VERTICAL, MUZZLE DOWN	_DK_
BARREL HORIZONTAL, BOTTOM DOWN	_0K
BARREL HORIZONTAL, BOTTOM UP	_OK_
BARREL HORIZONTAL, LEFT SIDE UP	_ok_
BARREL HORIZONTAL, RIGHT SIDE UP	ок
48 inch drop (safe <u>on</u>) note: drop is 48 inches from the center of gravity of the firearm	
BARREL VERTICAL, MUZZLE UP	<u>ok</u>
BARREL VERTICAL, MUZZLE DOWN	_ D K_
BARREL HORIZONTAL, BOTTOM DOWN	ok
BARREL HORIZONTAL, BOTTOM UP	OK
BARREL HORIZONTAL, LEFT SIDE UP	-OK-
BARREL HORIZONTAL, RIGHT SIDE UP	ОК '
"ROTATION TEST" BUTT ON MAT, LET FIREARM FALL TO LEFT AND RIGHT	
LEFT SIDE UP	<u>ok</u>
RIGHT SIDE UP	_ <u>&K_</u>