

NOTES ON
ABAR LIT. REVIEW.
STANT, 2.17.82

HIGH PRESSURE ABUSE 2ND QTR 8.8 RAD
IS THIS THE "MOTOR SETBACK IN RATE 88?"

← FULLY ADJUSTABLE

- WITHIN STOCK
- WITHIN SPEC LIMITS

~~SAAMI~~ DROP TEST INFO NEEDED

SAFETY ON/OFF FORCES SPEC

WOULD DEPEND ON ERGONOMICS AND
HUMAN MECH ADVANTAGE & STROKE

→ BELT LOCK WITH OVERRIDE

NOT RETROFITTABLE TO M200

DOOR WT - OR - POLL SPRINGS

LOW WT - OF - POLL - SPRING SPRING RATE
"K" LBS/INCH

SEALED FIRE CONTROL

RESISTANT TO EXTERNAL INFLUENCES

BALANCED TRIGGER

TRIGGER BLOCK AND SHOT BLOCK.

SYSTEMATIC LOOK @ M200 PRODUCTION
PROBLEMS NOW.

- TO CORRECT THEM,

ONLY DISengage BOLT LOCK
WHEN IN "S" POSITION?

→ You MUST BE IN S
TO OPEN BOLT

- FIRING PIN FOR DEFATTS
BOLT LOCK FOR NORMAL
REPEAT SHOTS.
[like the Newton rifle]

TO LIFT BOLT:

MOVE SAFETY TO "S"

OR

PULL TRIGGER

[]