

6.93 WAW

N BAR FIRE CONTROL

TRIGGER RETRACTION UPON PARTIAL
PULL IS IMPORTANT:

- M200 RELIES ON POWDERAGE
SPRING; NOT MAINSPRING

* THIS WOULD BE A CONCERN IN
ANY SYSTEM WHERE FRICTION ~~CAN~~
FORCE OPPOSING TRIGGER PULL IS GREATER
THAN THE SPRING COMPONENT OPPOSING
TRIGGER PULL.

GUNS COLT SAVER
• REL. BOLT LOCK
• TOGGLE TRIGGS

CHANGE S. U. F. SEQUENCE OF 3 POS SAFETY

U S F

~~LOW RATE SPRING~~

BOLT LOCK INDEPENDENT OF SAFETY-

LOCKED WHEN BOLT CLOSSED. DISABLED BY F. DN FALL

OR OVER-RIDE BUTTON.

TRIGGER BLOCK SAFETY: HOW TO MAINTAIN
TRIGGER/SAFETY RELATIONSHIP WHEN ADJUSTING
TRIGGER/SEAR RELATIONSHIP.

TRIGGER BLOCK

FIRST THING TO BE BLOCKED (F → S)

CARRIED INTO ^{SEAR} SUPPORT POSITION OR SAFETY WHEN MORE

LAST THING TO BE FREED (S → F)

F → S

CAM TRIGGER INTO SUPPORT POSITION

BLOCK IT THERE

CAM SEAR UP OFF OF TRIGGER

↓ CAM F.P. BACK

S TO F | RELEASE SEAR TO CONTACT TRIGGER
↓ UNBLOCK TRIGGER

INSERT TRIGGER & SEAL SUPPORT SURFACE
BROWING BED USE DULOW SCREEN MOUNT STEEL
PANEL INSERTED INTO THE TRIGGER.