

10.15.93
WAW

LIABILITY

POINT OF VIEW

HIGH

- AVOID PATENT INFRINGEMENT
- NOT INTERCHANGEABLE OR RETROFITTABLE TO M700
- TWO POSITION "S" & "F"
- SEALED UNIT; REQUIRING NO ORIGINAL OR FIELD LUBRICATION
- ROBUST AGAINST IMPACT - EXCEED SAAMI/ANSI RECOMMENDATIONS BY WIDE MARGIN
- USER OPERATION CONSISTENT WITH PRECEDENT AND CONVENTION.
- ROBUST AGAINST EFFECTS OF TAMPERING/ADJUSTING
- HIGHLY INTUITIVE OPERATION

MEDIUM

- READILY DEFENSIBLE REASONS FOR DEPARTURE FROM CURRENT DESIGN

? • CONVERTIBLE & REVERSIBLE BOLT LOCK

? • INTERLOCKS WILL NOT FIRE IF TRIGGER IS PULVED AND HELD AS SAFETY S → F

(1) SAFETY WON'T MOVE IF TRIGGER IS HELD DOWN
OR

(2) SAFETY - WON'T MOVE BUT TRIGGER MUST THEN BE RELEASED AND PULVED TO CAUSE FIRING.